RIGID LIGHT BARS

W Hi-Effi. 24V 160LED/M 8mm

TRU-BBJ24V

W Hi-Effi. 24V 160LED/M 8mm. Review the dimensions and electrical ratings for your installation.

Use this catalog sheet to discuss your project. Final dimensions, ratings, certifications and available configurations must be confirmed for the selected product.



Product specifications

Truled part number	TRU-BBJ24V
Category	Rigid strips
Product type	Rigid light bars
art No.	24-CV-160-44700R & 24-CV-160-44710A
Dimension	1000*8*2mm [39.3*0.31*0.08in.]
Increment	100mm [3.94in.]
LED Type	SMD 2835
LED Qty	160LED/M [49LED/ft.]
Voltage	24VDC
Power	14.4W/M [4.39W/ft.]
CCT / Wavelength	2700K/3000K/3500K/ 4000K/5000K/6500K 1600K/1800K/2000K/ 2200K/2400K/8000K/10000K Red/Green/Blue/Yellow/Orange/Purple/ Pink/Hyper Red/Emerald(light Green)/ Cyan(Ice Blue)/Amber/Golden/ Tiffany Blue/Magenta (Customized color are available)
Brightness @4000K&CRI90	2100lm/M [640lm/ft.]
Light Efficiency @4000K&CRI90	146lm/W

Beam Angle	120°
IP Rating	IP20 [Dry]
PCB Type	white, double-sided FR4 base & single-sided Alu base, 1.2mm [0.05in.] thickness, 2oz copper OSP

Request pricing & availability

Request a product quote at truled.com

Include any configuration reference, quantities, required lengths and project location.

A configuration reference identifies a published specification row. A row may list multiple options; it is not confirmation that every option is included. This sheet is not an installation instruction or an approved project submittal.