RIGID LIGHT BARS

W Hi-Eff. Free-Cutting 24V 120LED/M 8mm

TRU-BBO24V

W Hi-Eff. Free-Cutting 24V 120LED/M 8mm. Review the dimensions and electrical ratings for your installation.

Use this catalog sheet to discuss your project. Final dimensions, ratings, certifications and available configurations must be confirmed for the selected product.



Product specifications

Truled part number	TRU-BBO24V
Category	Rigid strips
Product type	Rigid light bars
Dimension	1000*8*2mm [39.3*0.31*0.08in.]
Increment	8.33mm [0.33in.]
LED Type	SMD 2835
LED Qty	120LED/M [37LED/ft.]
Voltage	24VDC
Power	9.6W/M [2.93W/ft.]
CCT / Wavelength	2700K/3000K/3500K/ 4000K/5000K/6500K 1600K/1800K/2000K/ 2200K/2400K/8000K/10000K Red/Green/Blue/Yellow/Orange/Purple/ Pink/Hyper Red/Emerald(light Green)/ Cyan(Ice Blue)/Amber/Golden/ Tiffany Blue/Magenta (Customized color are available)
Brightness @4000K&CRI90	1400lm/M [427lm/ft.]
Light Efficiency @4000K&CRI90	146lm/W
Beam Angle	120°

IP Rating	IP20 [Dry]
PCB Type	white, double-sided FR4 base & single-sided Alu base, 1.2mm [0.05in.] thickness, 2oz copper OSP

Request pricing & availability

Request a product quote at truled.com

Include any configuration reference, quantities, required lengths and project location.

A configuration reference identifies a published specification row. A row may list multiple options; it is not confirmation that every option is included. This sheet is not an installation instruction or an approved project submittal.