EUROPEAN DRIVERS

Driver of European Market Series

TRU-D-E

Driver of European Market Series. Review the dimensions and electrical ratings for your installation.

Use this catalog sheet to discuss your project. Final dimensions, ratings, certifications and available configurations must be confirmed for the selected product.



Product specifications

Truled part number	TRU-D-E
Category	Drivers
Product type	European drivers

Configuration reference

TRU-D-E-A

Power	20W
Input Voltage	220-240 VAC/DC
Output Voltage	DC24V
Dimension (L*W*H)	L129*W50*H13.5 (L5.1*W2*H0.5in.)
Listed certifications	CE, ENEC, UKCA, RCM, EL

Configuration reference

TRU-D-E-B

Power	30W
Input Voltage	220-240 VAC/DC
Output Voltage	DC24V
Dimension (L*W*H)	L129*W50*H13.5 (L5.1*W2*H0.5in.)
Listed certifications	CE, ENEC, UKCA, RCM, EL

Configuration reference

TRU-D-E-C

Power	48W
Input Voltage	220-240 VAC/DC
Output Voltage	DC24V
Dimension (L*W*H)	L160*W57.5*H18 (L6.3*W2.3*H0.7in.)
Listed certifications	CE, ENEC, UKCA, RCM, EL

Configuration reference

TRU-D-E-D

Power	60W
Input Voltage	220-240 VAC/DC
Output Voltage	DC24V
Dimension (L*W*H)	L160*W57.5*H18 (L6.3*W2.3*H0.7in.)
Listed certifications	CE, ENEC, UKCA, RCM, EL

Configuration reference

TRU-D-E-E

Power	72W
Input Voltage	220-240 VAC/DC
Output Voltage	DC24V
Dimension (L*W*H)	L185*W63.5*H22 (L7.3*W2.5*H0.9in.)
Listed certifications	CE, ENEC, UKCA, RCM, EL

Configuration reference

TRU-D-E-F

Power	100W
Input Voltage	220-240 VAC/DC
Output Voltage	DC24V
Dimension (L*W*H)	L185*W63.5*H22 (L7.3*W2.5*H0.9in.)
Listed certifications	CE, ENEC, UKCA, RCM, EL

Configuration reference

TRU-D-E-G

Power	36W
Input Voltage	220-240 VAC/DC
Output Voltage	DC24V
Dimension (L*W*H)	L245*W30*H21 (L9.6*W1.2*H0.8in.)
Listed certifications	CE, ENEC, RCM, UKCA, CCC

Configuration reference

TRU-D-E-H

Power	36W
Input Voltage	220-240 VAC/DC
Output Voltage	DC48V
Dimension (L*W*H)	L245*W30*H21 (L9.6*W1.2*H0.8in.)
Listed certifications	CE, ENEC, RCM, UKCA, CCC

Configuration reference

TRU-D-E-I

Power	60W
Input Voltage	220-240 VAC/DC
Output Voltage	DC24V
Dimension (L*W*H)	L245*W30*H21 (L9.6*W1.2*H0.8in.)
Listed certifications	CE, ENEC, RCM, UKCA, CCC

Configuration reference

TRU-D-E-J

Power	57.6W
Input Voltage	220-240 VAC/DC
Output Voltage	DC48V
Dimension (L*W*H)	L285*W30*H21 (L11.2*W1.2*H0.8in.)
Listed certifications	CE, ENEC, RCM, UKCA, CCC

Configuration reference

TRU-D-E-K

Power	100W
Input Voltage	220-240 VAC/DC
Output Voltage	DC24V
Dimension (L*W*H)	L355*W30*H21 (L14*W1.2*H0.8in.)
Listed certifications	CE, ENEC, RCM, UKCA, CCC

Configuration reference

TRU-D-E-L

Power	100W
Input Voltage	220-240 VAC/DC
Output Voltage	DC48V
Dimension (L*W*H)	L355*W30*H21 (L14*W1.2*H0.8in.)
Listed certifications	CE, ENEC, RCM, UKCA, CCC

Configuration reference

TRU-D-E-M

Power	150W
Input Voltage	220-240 VAC/DC
Output Voltage	DC24V
Dimension (L*W*H)	L355*W36*H23 (L14*W1.4*H0.9in.)
Listed certifications	CE, ENEC, RCM, UKCA, CCC

Configuration reference

TRU-D-E-N

Power	150W
Input Voltage	220-240 VAC/DC
Output Voltage	DC48V
Dimension (L*W*H)	L355*W36*H23 (L14*W1.4*H0.9in.)
Listed certifications	CE, ENEC, RCM, UKCA, CCC

Configuration reference

TRU-D-E-O

Power	36W
Input Voltage	220-240 VAC/DC
Output Voltage	DC24V
Dimension (L*W*H)	L245*W30*H21 (L9.6*W1.2*H0.8in.)
Listed certifications	CE, ENEC, UKCA, RCM, DALI-2, CCC

Configuration reference

TRU-D-E-P

Power	36W
Input Voltage	220-240 VAC/DC
Output Voltage	DC48V
Dimension (L*W*H)	L245*W30*H21 (L9.6*W1.2*H0.8in.)
Listed certifications	CE, ENEC, UKCA, RCM, DALI-2, CCC

Configuration reference

TRU-D-E-Q

Power	60W
Input Voltage	220-240 VAC/DC
Output Voltage	DC24V
Dimension (L*W*H)	L285*W30*H21 (L11.2*W1.2*H0.8in.)
Listed certifications	CE, ENEC, UKCA, RCM, DALI-2, CCC

Configuration reference

TRU-D-E-R

Power	57.6W
Input Voltage	220-240 VAC/DC
Output Voltage	DC48V
Dimension (L*W*H)	L285*W30*H21 (L11.2*W1.2*H0.8in.)
Listed certifications	CE, ENEC, UKCA, RCM, DALI-2, CCC

Configuration reference

TRU-D-E-S

Power	100W
Input Voltage	220-240 VAC/DC
Output Voltage	DC24V
Dimension (L*W*H)	L355*W30*H21 (L14*W1.2*H0.8in.)
Listed certifications	CE, ENEC, UKCA, RCM, DALI-2, CCC

Configuration reference

TRU-D-E-T

Power	100W
Input Voltage	220-240 VAC/DC
Output Voltage	DC48V
Dimension (L*W*H)	L355*W30*H21 (L14*W1.2*H0.8in.)
Listed certifications	CE, ENEC, UKCA, RCM, DALI-2, CCC

Configuration reference

TRU-D-E-U

Power	150W
Input Voltage	220-240 VAC/DC
Output Voltage	DC24V
Dimension (L*W*H)	L355*W36*H23 (L14*W1.4*H0.9in.
Listed certifications	CE, ENEC, UKCA, RCM, DALI-2, CCC

Configuration reference

TRU-D-E-V

Power	150W
Input Voltage	220-240 VAC/DC
Output Voltage	DC48V
Dimension (L*W*H)	L355*W36*H23 (L14*W1.4*H0.9in.
Listed certifications	CE, ENEC, UKCA, RCM, DALI-2, CCC

Configuration reference

TRU-D-E-W

Power	100W
Input Voltage	220-240 VAC/DC
Output Voltage	DC24V
Dimension (L*W*H)	L355*W36*H23 (L14*W1.4*H0.9in.)
Listed certifications	CE, ENEC, UKCA, RCM, DALI-2

Configuration reference

TRU-D-E-X

Power	150W
Input Voltage	220-240 VAC/DC
Output Voltage	DC24V
Dimension (L*W*H)	L355*W36*H23 (L14*W1.4*H0.9in.)
Listed certifications	CE, ENEC, UKCA, RCM, DALI-2

Configuration reference

TRU-D-E-Y

Power	150W
Input Voltage	220-240 VAC/DC
Output Voltage	DC24V
Dimension (L*W*H)	L190*W68*H38 (L7.5*W2.7*H1.5in.)
Listed certifications	CE, ENEC, UKCA, RCM, CCC, DALI-1, EL

Configuration reference

TRU-D-E-Z

Power	150W
Input Voltage	220-240 VAC/DC
Output Voltage	DC48V
Dimension (L*W*H)	L190*W68*H38 (L7.5*W2.7*H1.5in.)
Listed certifications	CE, ENEC, UKCA, RCM, CCC, DALI-1, EL

Configuration reference

TRU-D-E-AA

Power	240W
Input Voltage	220-240 VAC/DC
Output Voltage	DC24V
Dimension (L*W*H)	L221*W68*H38 (L8.7*W2.7*H1.5in.)
Listed certifications	CE, ENEC, UKCA, RCM, CCC, DALI-1, EL

Configuration reference

TRU-D-E-AB

Power	240W
Input Voltage	220-240 VAC/DC
Output Voltage	DC48V
Dimension (L*W*H)	L221*W68*H38 (L8.7*W2.7*H1.5in.)
Listed certifications	CE, ENEC, UKCA, RCM, CCC, DALI-1, EL

Configuration reference

TRU-D-E-AC

Power	300W
Input Voltage	220-240 VAC/DC
Output Voltage	DC24V
Dimension (L*W*H)	L218*W89.5*H46 (L8.6*W3.5*H1.8in.)
Listed certifications	CE, ENEC, UKCA, RCM, CCC, DALI-1, EL

Configuration reference

TRU-D-E-AD

Power	300W
Input Voltage	220-240 VAC/DC
Output Voltage	DC48V
Dimension (L*W*H)	L218*W89.5*H46 (L8.6*W3.5*H1.8in.)
Listed certifications	CE, ENEC, UKCA, RCM, CCC, DALI-1, EL

Configuration reference

TRU-D-E-AE

Power	150W
Input Voltage	220-240 VAC/DC
Output Voltage	DC24V
Dimension (L*W*H)	L213*W68*H38 (L8.4*W2.7*H1.5in.)
Listed certifications	CE, ENEC, UKCA, RCM, CCC, DALI-2, EL

Configuration reference

TRU-D-E-AF

Power	150W
Input Voltage	220-240 VAC/DC
Output Voltage	DC48V
Dimension (L*W*H)	L213*W68*H38 (L8.4*W2.7*H1.5in.)
Listed certifications	CE, ENEC, UKCA, RCM, CCC, DALI-2, EL

Configuration reference

TRU-D-E-AG

Power	240W
Input Voltage	220-240 VAC/DC
Output Voltage	DC24V
Dimension (L*W*H)	L253*W68*H38 (L10*W2.7*H1.5in.)
Listed certifications	CE, ENEC, UKCA, RCM, CCC, DALI-2, EL

Configuration reference

TRU-D-E-AH

Power	240W
Input Voltage	220-240 VAC/DC
Output Voltage	DC48V
Dimension (L*W*H)	L253*W68*H38 (L10*W2.7*H1.5in.)
Listed certifications	CE, ENEC, UKCA, RCM, CCC, DALI-2, EL

Configuration reference

TRU-D-E-AI

Power	300W
Input Voltage	220-240 VAC/DC
Output Voltage	DC24V
Dimension (L*W*H)	L252*W89.5*H46 (L9.9*W3.5*H1.8in.)
Listed certifications	CE, ENEC, UKCA, RCM, CCC, DALI-2, EL

Configuration reference

TRU-D-E-AJ

Power	300W
Input Voltage	220-240 VAC/DC
Output Voltage	DC48V
Dimension (L*W*H)	L252*W89.5*H46 (L9.9*W3.5*H1.8in.)
Listed certifications	CE, ENEC, UKCA, RCM, CCC, DALI-2, EL

Configuration reference

TRU-D-E-AK

Power	150W
Input Voltage	220-240 VAC/DC
Output Voltage	DC24V
Dimension (L*W*H)	L213*W68*H38 (L8.4*W2.7*H1.5in.)
Listed certifications	CE, ENEC, UKCA, RCM, CCC, DALI-2, EL

Configuration reference

TRU-D-E-AL

Power	150W
Input Voltage	220-240 VAC/DC
Output Voltage	DC48V
Dimension (L*W*H)	L213*W68*H38 (L8.4*W2.7*H1.5in.)
Listed certifications	CE, ENEC, UKCA, RCM, CCC, DALI-2, EL

Configuration reference

TRU-D-E-AM

Power	300W
Input Voltage	220-240 VAC/DC
Output Voltage	DC24V
Dimension (L*W*H)	L252*W89.5*H46 (L9.9*W3.5*H1.8in.)
Listed certifications	CE, ENEC, UKCA, RCM, CCC, DALI-2, EL

Request pricing & availability

Request a product quote at truled.com

Include any configuration reference, quantities, required lengths and project location.

A configuration reference identifies a published specification row. A row may list multiple options; it is not confirmation that every option is included. This sheet is not an installation instruction or an approved project submittal.