HIGH-VOLTAGE STRIPS

230VAC Standard&White

TRU-HSC

230VAC Standard&White. Review the dimensions and electrical ratings for your installation.

Use this catalog sheet to discuss your project. Final dimensions, ratings, certifications and available configurations must be confirmed for the selected product.



Product specifications

Truled part number	TRU-HSC
Category	High voltage
Product type	High-voltage strips
Dimension	W16.5*H7mm [W0.65*H0.28in.]
Max. Length	50M [164ft.]
Increment	500mm [1.64ft.]
LED Type	SMD2835 / 3 Step 1 Bin
LED Qty	120LED/M [36LED/ft.]
Voltage	230VAC
Power	6W/M [1.83W/ft.]
CCT / Wavelength	2700K±120K 3000K±150K 3500K±300K 4000K±300K 5000K±400K 6500K±500K
Brightness @4000K&CRI80	450-550lm/M [140-155lm/ft.]
Light Efficiency @4000K&CRI80	75-85lm/W
Brightness @4000K&CRI90	360-440lm/M [110-134lm/ft.]

Light Efficiency @4000K&CRI90	60-73lm/W
Beam Angle	120°
IP Rating	IP40 / IP65

Request pricing & availability

Request a product quote at truled.com

Include any configuration reference, quantities, required lengths and project location.

A configuration reference identifies a published specification row. A row may list multiple options; it is not confirmation that every option is included. This sheet is not an installation instruction or an approved project submittal.