HIGH-VOLTAGE STRIPS

120VAC Dimmable&Colorful

TRU-HSG

120VAC Dimmable&Colorful. Review the dimensions and electrical ratings for your installation.

Use this catalog sheet to discuss your project. Final dimensions, ratings, certifications and available configurations must be confirmed for the selected product.



Product specifications

Truled part number	TRU-HSG
Category	High voltage
Product type	High-voltage strips

Configuration reference

TRU-HSG-A

Dimension	W18.5*H8.5mm [W0.73*H0.33in]
Max. Length	50M [164ft.]
Increment	100mm [4in.]
LED Type	SMD2835
LED Qty	80LED/M [24LED/ft.]
Voltage	120VAC
PF	>0.97
Power	9W/M [2.7W/ft.]
CCT / Wavelength	Red: 621-635nm (lambda d) Green: 515-530nm (lambda d) Blue: 450-460nm (lambda d) Amber: 585-595nm (lambda d) Pink: \
Brightness & Light Efficiency	Red: 134lm/M [41lm/ft.] & 15lm/W Green: 936lm/M [285lm/ft.] & 104lm/W Blue: 135lm/M [41lm/ft.] & 15lm/W Amber: 502lm/M [153lm/ft.] & 56lm/W Pink: 413lm/M [126lm/ft.] & 46lm/W
Beam Angle	120°
IP Rating	IP65 Damp (indoor for moisture, outdoor for being covered) IP65 Wet (outdoor for water spray & rain)

Configuration reference

TRU-HSG-B

Dimension	W18.5*H8.5mm [W0.73*H0.33in]
Max. Length	50M [164ft.]
Increment	Not specified
LED Type	Not specified
LED Qty	Not specified
Voltage	Not specified
PF	Not specified
Power	Not specified
CCT / Wavelength	Not specified
Brightness & Light Efficiency	Not specified
Beam Angle	Not specified
IP Rating	Not specified

Request pricing & availability

Request a product quote at truled.com

Include any configuration reference, quantities, required lengths and project location.

A configuration reference identifies a published specification row. A row may list multiple options; it is not confirmation that every option is included. This sheet is not an installation instruction or an approved project submittal.