HIGH-VOLTAGE STRIPS

120VAC Dynamic White

TRU-HSH

120VAC Dynamic White. Review the dimensions and electrical ratings for your installation.

Use this catalog sheet to discuss your project. Final dimensions, ratings, certifications and available configurations must be confirmed for the selected product.



Product specifications

Truled part number	TRU-HSH
Category	High voltage
Product type	High-voltage strips
No.	TRU-HSG-0018-0015
Dimension	W18.5*H8.5mm [W0.73*H0.33in.]
Max. Length	50M [164ft.]
Increment	150mm [6in.]
LED Type	SMD2835 / 3 Step 1 Bin
LED Qty	120LED/M [36LED/ft.]
Voltage	120VAC
PF	>0.99
THD	<15%
Power	12W/M [3.66W/ft.]
CCT / Wavelength	Dynamic White (2700~5000K or 1800~3000K D2W)

Brightness @5000K&CRI80	1260lm/M [384lm/ft.]
Light Efficiency @5000K&CRI80	105lm/W
Brightness @5000K&CRI90	1050lm/M [320lm/ft.]
Light Efficiency @5000K&CRI90	88lm/W
Beam Angle	120°
IP Rating	IP65 Damp (indoor for moisture, outdoor for being covered) IP65 Wet (outdoor for water spray & rain)

Request pricing & availability

Request a product quote at truled.com

Include any configuration reference, quantities, required lengths and project location.

A configuration reference identifies a published specification row. A row may list multiple options; it is not confirmation that every option is included. This sheet is not an installation instruction or an approved project submittal.