CABINET LIGHTING

Pro Series

TRU-LBAE24V

Pro Series. Review the dimensions and electrical ratings for your installation.

Use this catalog sheet to discuss your project. Final dimensions, ratings, certifications and available configurations must be confirmed for the selected product.



Product specifications

Truled part number	TRU-LBAE24V
Category	Linear lighting
Product type	Cabinet lighting
Power	7W/M [2.13W/ft.]
Voltage	24VDC
CRI	>=90
CCT / Wavelength	2700K±120K/ 3000K±150K/ 4000K±300K/ 5000K±500K
Brightness @3000K&CRI90	315lm/M [96lm/ft.]
Light Efficiency @3000K&CRI90	45lm/W
Beam Angle	120°

Configuration reference

TRU-LBAE24V-A

Dimension	L282xW7xH9mm [L11.1*W0.28*H0.35in.]
LED Type	SMD 2216
LED Q'ty	320LED/M [97LED/ft.]
ncrement Length	25mm [0.98in.]
Appearance Color	Grey/Black
Installation Method	Recessed Mounting
IP Rating	IP20 [Dry]
Operating Ambient	20~45°C
Lifespan/ Warranty	50,000H* 5 years

Configuration reference

TRU-LBAE24V-B

Dimension	L582xW7xH9mm [L22.91*W0.28*H0.35in.]
LED Type	SMD 2216
LED Q'ty	320LED/M [97LED/ft.]
ncrement Length	25mm [0.98in.]
Appearance Color	Grey/Black
Installation Method	Recessed Mounting
IP Rating	IP20 [Dry]
Operating Ambient	20~45°C
Lifespan/ Warranty	50,000H* 5 years

Configuration reference

TRU-LBAE24V-C

Dimension	L882xW7xH9mm [L34.72*W0.28*H0.35in.]
LED Type	SMD 2216
LED Q'ty	320LED/M [97LED/ft.]
ncrement Length	25mm [0.98in.]
Appearance Color	Grey/Black
Installation Method	Recessed Mounting
IP Rating	IP20 [Dry]
Operating Ambient	20~45°C
Lifespan/ Warranty	50,000H* 5 years

Configuration reference

TRU-LBAE24V-D

Dimension	L1032xW7xH9mm [L40.63*W0.28*H0.35in.]
LED Type	SMD 2216
LED Q'ty	320LED/M [97LED/ft.]
ncrement Length	25mm [0.98in.]
Appearance Color	Grey/Black
Installation Method	Recessed Mounting
IP Rating	IP20 [Dry]
Operating Ambient	20~45°C
Lifespan/ Warranty	50,000H* 5 years

Configuration reference

TRU-LBAE24V-E

Dimension	L1182xW7xH9mm [L46.54*W0.28*H0.35in.]
LED Type	SMD 2216
LED Q'ty	320LED/M [97LED/ft.]
ncrement Length	25mm [0.98in.]
Appearance Color	Grey/Black
Installation Method	Recessed Mounting
IP Rating	IP20 [Dry]
Operating Ambient	20~45°C
Lifespan/ Warranty	50,000H* 5 years

Configuration reference

TRU-LBAE24V-F

Dimension	L1532xW7xH9mm [L60.31*W0.28*H0.35in.]
LED Type	SMD 2216
LED Q'ty	320LED/M [97LED/ft.]
ncrement Length	25mm [0.98in.]
Appearance Color	Grey/Black
Installation Method	Recessed Mounting
IP Rating	IP20 [Dry]
Operating Ambient	20~45°C
Lifespan/ Warranty	50,000H* 5 years

Request pricing & availability

Request a product quote at truled.com

Include any configuration reference, quantities, required lengths and project location.

A configuration reference identifies a published specification row. A row may list multiple options; it is not confirmation that every option is included. This sheet is not an installation instruction or an approved project submittal.