UNDERWATER NEON FLEX

Swimming Pool · Top-Bend & Side-Bend neon flex

TRU-NAB24V

Swimming Pool · Top-Bend & Side-Bend neon flex. Review the dimensions and electrical ratings for your installation.

Use this catalog sheet to discuss your project. Final dimensions, ratings, certifications and available configurations must be confirmed for the selected product.



Product specifications

Truled part number	TRU-NAB24V
Category	Neon flex
Product type	Underwater neon flex
Style	Side-Bend (White Swimming Pool Underwater)
Dimension	W13xH13mm [W0.51xH0.51in.]
Max. Run Length	5M [16.4ft.]
Increment	Free-cutting to be any length
LED Type	SMD2835
LED Qty	120LED/M [37LED/ft.]
Voltage	DC24V
Power	12W/M [3.66W/ft.]
CCT/Wavelength	2700K±120K 3000K±150K 3500K±300K 4000K±300K 5000K±400K 6000K±500K
Brightness @4000K&CRI80	972lm/M [296lm/ft.]
Light Efficiency @4000K&CRI80	81lm/W

Brightness @4000K&CRI90	830m/M [253lm/ft.]
Light Efficiency @4000K&CRI90	69lm/W
Beam Angle	120°
IP&IK Rating	IP68/IP69K [Wet] (Max.3M underwater) & IK07

Configuration reference

TRU-NAB24V-A

Style	Top-Bend (White Swimming Pool Underwater)
Dimension	W13xH13mm [W0.51xH0.51in.]
Max. Run Length	5M [16.4ft.]
Increment	Free-cutting to be any length
LED Type	SMD2835
LED Qty	120LED/M [37LED/ft.]
Voltage	DC24V
Power	14W/M [4.27W/ft.]
CCT/Wavelength	2700K±120K 3000K±150K 3500K±300K 4000K±300K 5000K±400K 6000K±500K
Brightness @4000K&CRI80	1316lm/M [401lm/ft.]
Light Efficiency @4000K&CRI80	94lm/W
Brightness @4000K&CRI90	1120lm/M [341lm/ft.]
Light Efficiency @4000K&CRI90	80lm/W
Beam Angle	120°
IP&IK Rating	IP68/IP69K [Wet] (Max.3M underwater) & IK07

Configuration reference

TRU-NAB24V-B

Style	Top-Bend (White Swimming Pool Underwater)
Dimension	W13xH13mm [W0.51xH0.51in.]
Max. Run Length	5M [16.4ft.]
Increment	Free-cutting to be any length
LED Type	SMD2835
LED Qty	120LED/M [37LED/ft.]
Voltage	DC24V
Power	*10W/M [3.05W/ft.]
CCT/Wavelength	2700K±120K 3000K±150K 3500K±300K 4000K±300K 5000K±400K 6000K±500K
Brightness @4000K&CRI80	972lm/M [298 lm/ft.]
Light Efficiency @4000K&CRI80	94lm/W
Brightness @4000K&CRI90	830lm/M [253 lm/ft.]
Light Efficiency @4000K&CRI90	80lm/W
Beam Angle	120°
IP&IK Rating	IP68/IP69K [Wet] (Max.3M underwater) & IK07

Request pricing & availability

Request a product quote at truled.com

Include any configuration reference, quantities, required lengths and project location.

A configuration reference identifies a published specification row. A row may list multiple options; it is not confirmation that every option is included. This sheet is not an installation instruction or an approved project submittal.