DUAL-BEND NEON FLEX

360° Luminous · Dual-Bend · diameter 13FC neon flex

TRU-NDB24V

360° Luminous · Dual-Bend · diameter 13FC neon flex. Review the dimensions and electrical ratings for your installation.

Use this catalog sheet to discuss your project. Final dimensions, ratings, certifications and available configurations must be confirmed for the selected product.



Product specifications

Truled part number	TRU-NDB24V
Category	Neon flex
Product type	Dual-bend neon flex
Style	Dual-Bend (White 360° Luminous)
Dimension	diameter 13mm [diameter 0.51in.]
Max. Run Length & Max. Shipping Length	5M [16.4ft.] & 10M [32.8ft.]
Increment	free-cutting to be any length
LED Type	SMD 2216
Voltage	24VDC
Power	10W/M [3.05W/ft.]
CCT / Wavelength	2700K±120K 3000K±150K 3500K±300K 4000K±300K 5000K±400K 6000K±500K
Brightness @4000K&CRI90	760lm/M [232lm/ft.]
Light Efficiency @4000K&CRI90	76lm/W
Beam Angle	360°

IP&IK Rating	IP67 [wet] & IK06

Request pricing & availability

Request a product quote at truled.com

Include any configuration reference, quantities, required lengths and project location.

A configuration reference identifies a published specification row. A row may list multiple options; it is not confirmation that every option is included. This sheet is not an installation instruction or an approved project submittal.