DUAL-BEND NEON FLEX

360° Luminous Poseable · Dual-Bend · diameter 25FC neon flex

TRU-NDF24V

360° Luminous Poseable · Dual-Bend · diameter 25FC neon flex. Review the dimensions and electrical ratings for your installation.

Use this catalog sheet to discuss your project. Final dimensions, ratings, certifications and available configurations must be confirmed for the selected product.



Product specifications

Truled part number	TRU-NDF24V
Category	Neon flex
Product type	Dual-bend neon flex
Style	Dual-Bend (White 360° Luminous Poseable)
Dimension	diameter 25mm [diameter 0.98in.]
Max. Run Length & Max. Shipping Length	5M [16.4ft.] & 5M [16.4ft.]
Increment	Free-cutting to be any length (Factory made only)
LED Type	SMD 2835
Voltage	24VDC
Power	20W/M [6.1W/ft.]
CCT / Wavelength	2700K±120K 3000K±150K 4000K±300K 5000K±400K 6000K±500K
Brightness @4000K&CRI90	1300lm/M [396lm/ft.]
Light Efficiency @4000K&CRI90	65lm/W

Beam Angle	360°
IP Rating	IP67 [wet] & IK07

Request pricing & availability

Request a product quote at truled.com

Include any configuration reference, quantities, required lengths and project location.

A configuration reference identifies a published specification row. A row may list multiple options; it is not confirmation that every option is included. This sheet is not an installation instruction or an approved project submittal.