DUAL-BEND NEON FLEX

Dual-Bend neon flex

TRU-NDG24V

Dual-Bend neon flex. Review the dimensions and electrical ratings for your installation.

Use this catalog sheet to discuss your project. Final dimensions, ratings, certifications and available configurations must be confirmed for the selected product.



Product specifications

Truled part number	TRU-NDG24V
Category	Neon flex
Product type	Dual-bend neon flex

Configuration reference

TRU-NDG24V-A

Style	Dual-Bend (White) 4-Sided Black Jacket
Dimension	W16xH16mm [W0.63xH0.63in.]
Max. Run Length & Max. Shipping Length	5M [16.4ft.] & 50M [164ft.]
Increment	Free-cutting to be any length
LED Type	SMD2835
LED Qty	140LED/M [43LED/ft.]
Voltage	DC24V
Power	14W/M [4.27W/ft.]
CCT/Wavelength	2700K±150K 3000K±200K 4000K±350K
Brightness @4000K&CRI80	182lm/M [55lm/ft.]
Light Efficiency @4000K&CRI80	13lm/W
Brightness @4000K&CRI90	154lm/M [47lm/ft.]
Light Efficiency @4000K&CRI90	11lm/W
Beam Angle	90°
IP&IK Rating	IP67 [Wet] & IK06

Configuration reference

TRU-NDG24V-B

Style	Dual-Bend (RGB) 4-Sided Black Jacket
Dimension	W16xH16mm [W0.63xH0.63in.]
Max. Run Length & Max. Shipping Length	5M [16.4ft.] & 50M [164ft.]
Increment	50mm [1.97in.]
LED Type	SMD2835
LED Qty	120LED/M [37LED/ft.]
Voltage	DC24V
Power	14W/M [4.27W/ft.]
CCT/Wavelength	R: 620-630nm G: 515-530nm B: 460-470nm
Brightness @4000K&CRI80	Mix: 49lm/M [15lm/ft.]
Light Efficiency @4000K&CRI80	Mix: 3.5lm/W
Brightness @4000K&CRI90	Not specified
Light Efficiency @4000K&CRI90	Not specified
Beam Angle	90°
IP&IK Rating	IP67 [Wet] & IK06

Configuration reference

TRU-NDG24V-C

Style	Dual-Bend (SPI RGB) 4-Sided Black Jacket
Dimension	W16xH16mm [W0.63xH0.63in.]
Max. Run Length & Max. Shipping Length	5M [16.4ft.] & 10M [32.8ft.]
Increment	50mm [1.97in.]
LED Type	SMD2835
LED Qty	120LED/M [37LED/ft.]
Voltage	DC24V
Power	14W/M [4.27W/ft.]
CCT/Wavelength	R: 620-630nm G: 515-530nm B: 460-470nm
Brightness @4000K&CRI80	Mix: 49lm/M [15lm/ft.]
Light Efficiency @4000K&CRI80	Mix: 3.5lm/W
Brightness @4000K&CRI90	Not specified
Light Efficiency @4000K&CRI90	Not specified
Beam Angle	90°
IP&IK Rating	IP67 [Wet] & IK06

Request pricing & availability

Request a product quote at truled.com

Include any configuration reference, quantities, required lengths and project location.

A configuration reference identifies a published specification row. A row may list multiple options; it is not confirmation that every option is included. This sheet is not an installation instruction or an approved project submittal.