DUAL-BEND NEON FLEX

Dual-Bend neon flex

TRU-NDI24V

Dual-Bend neon flex. Review the dimensions and electrical ratings for your installation.

Use this catalog sheet to discuss your project. Final dimensions, ratings, certifications and available configurations must be confirmed for the selected product.



Product specifications

Truled part number	TRU-NDI24V
Category	Neon flex
Product type	Dual-bend neon flex
Style	Dual-Bend (White)
Dimension	W8xH8mm [W0.3xH0.3in.]
Max. Run Length & Max. Shipping Length	5M [16.4ft.] (Power fed on one side) & 15M [49.2ft.]
Increment	8.3mm [0.3in.] (Refer to the cutting instructions for details)
LED Type	SMD 2216
LED Qty	240LED/M [73LED/ft.]
Voltage	DC24V
Power	8W/M [2.44W/ft.]
CCT / Wavelength	2700K±120K 3000K±150K 3500K±300K 4000K±300K 5000K±400K 6000K±500K (LED is 3-step SDCM in one bin)
Brightness @4000K&CRI90	512lm/M [156lm/ft.]
Light Efficiency @4000K&CRI90	64lm/W

Beam Angle	120°
IP&IK Rating	IP67 [Wet] & IK06

Request pricing & availability

Request a product quote at truled.com

Include any configuration reference, quantities, required lengths and project location.

A configuration reference identifies a published specification row. A row may list multiple options; it is not confirmation that every option is included. This sheet is not an installation instruction or an approved project submittal.