
DUAL-BEND NEON FLEX

Artistic Decoration · Dual-Bend neon flex

TRU-NDK24V

Artistic Decoration · Dual-Bend neon flex. Review the dimensions and electrical ratings for your installation.

Use this catalog sheet to discuss your project. Final dimensions, ratings, certifications and available configurations must be confirmed for the selected product.



Product specifications

Truled part number	TRU-NDK24V
Category	Neon flex
Product type	Dual-bend neon flex

Configuration reference

TRU-NDK24V-A

Style	Dual-Bend (White) Black Jacket
Dimension	W16xH16mm [W0.63xH0.63in.]
Max. Run Length & Max. Shipping Length	5M [16.4ft.] (Power fed on one side) & 5M [16.4ft.]
Increment	Free-cutting to be any Length
LED Type	SMD 2835
LED Qty	120LED/M [36LED/ft.]
Voltage	DC24V
Power	14W/M [4.27W/ft.]
CCT / Wavelength	2700K±120K 3000K±150K 3500K±300K 4000K±300K 5000K±400K 6000K±500K (LED is 3-step SDCM in one bin)
Style of Replaceable Cover	Single Color In Red / Green / Blue / White
Beam Angle	120°
IP&IK Rating	IP67 [Wet] (End cap sealed by die-casting process) / IP54 [Damp] (End cap sealed by gluing process) & IK06

Configuration reference

TRU-NDK24V-B

Style	Dual-Bend (White High-Efficacy Premium) Black Jacket
Dimension	W16xH16mm [W0.63xH0.63in.]
Max. Run Length & Max. Shipping Length	5M [16.4ft.] (Power fed on one side) & 5M [16.4ft.]
Increment	50mm [1.97in.]
LED Type	SMD 2835
LED Qty	120LED/M [36LED/ft.]
Voltage	DC24V
Power	14W/M [4.27W/ft.]
CCT / Wavelength	2700K±120K 3000K±150K 3500K±300K 4000K±300K 5000K±400K 6000K±500K (LED is 3-step SDCM in one bin)
Style of Replaceable Cover	Single Color In Red / Green / Blue / White
Beam Angle	120°
IP&IK Rating	IP67 [Wet] (End cap sealed by die-casting process) / IP54 [Damp] (End cap sealed by gluing process) & IK06

Configuration reference

TRU-NDK24V-C

Style	Dual-Bend (CCT) Black Jacket
Dimension	W16xH16mm [W0.63xH0.63in.]
Max. Run Length & Max. Shipping Length	5M [16.4ft.] (Power fed on one side) & 5M [16.4ft.]
Increment	50mm [1.97in.]
LED Type	SMD 2216
LED Qty	240LED/M [73LED/ft.]
Voltage	DC24V
Power	14W/M [4.27W/ft.]
CCT / Wavelength	2700-6000K CCT-Tunable (LED is 3-step SDCM in one bin)
Style of Replaceable Cover	Single Color In Red / Green / Blue / White
Beam Angle	120°
IP&IK Rating	IP67 [Wet] (End cap sealed by die-casting process) / IP54 [Damp] (End cap sealed by gluing process) & IK06

Configuration reference

TRU-NDK24V-D

Style	Dual-Bend (RGB) Black Jacket
Dimension	W16xH16mm [W0.63xH0.63in.]
Max. Run Length & Max. Shipping Length	5M [16.4ft.] (Power fed on one side) & 5M [16.4ft.]
Increment	50mm [1.97in.]
LED Type	SMD 2835
LED Qty	120LED/M [36LED/ft.]
Voltage	DC24V
Power	14W/M [4.27W/ft.]
CCT / Wavelength	R: 615-625nm G: 515-530nm B: 460-470nm
Style of Replaceable Cover	Number / Character / Text / Pattern
Beam Angle	120°
IP&IK Rating	IP67 [Wet] (End cap sealed by die-casting process) / IP54 [Damp] (End cap sealed by gluing process) & IK06

Configuration reference

TRU-NDK24V-E

Style	Dual-Bend (RGBW) Black Jacket
Dimension	W16xH16mm [W0.63xH0.63in.]
Max. Run Length & Max. Shipping Length	5M [16.4ft.] (Power fed on one side) & 5M [16.4ft.]
Increment	62.5mm [2.46in.]
LED Type	SMD 5050
LED Qty	96LED/M [29LED/ft.]
Voltage	DC24V
Power	14W/M [4.27W/ft.]
CCT / Wavelength	R: 615-625nm G: 515-530nm B: 460-470nm W: 2700-6000K
Style of Replaceable Cover	Number / Character / Text / Pattern
Beam Angle	120°
IP&IK Rating	IP67 [Wet] (End cap sealed by die-casting process) / IP54 [Damp] (End cap sealed by gluing process) & IK06

Request pricing & availability

Request a product quote at truled.com

Include any configuration reference, quantities, required lengths and project location.

A configuration reference identifies a published specification row. A row may list multiple options; it is not confirmation that every option is included. This sheet is not an installation instruction or an approved project submittal.