DUAL-BEND NEON FLEX

Welding-Free Quick-Assembly Dual-Bend neon flex

TRU-NDL24V

Welding-Free Quick-Assembly Dual-Bend neon flex. Review the dimensions and electrical ratings for your installation.

Use this catalog sheet to discuss your project. Final dimensions, ratings, certifications and available configurations must be confirmed for the selected product.



Product specifications

Truled part number	TRU-NDL24V
Category	Neon flex
Product type	Dual-bend neon flex
Style	Dual-Bend (White)
Dimension	W16xH16mm [W0.63XH0.63in]
Max. Run Length & Max. Shipping Length	5M [16.4ft] & 50M [164ft]
Increment	Free-cutting to be any length
LED Type	SMD 2835
LED Qty	120LED/M [36LED/ft.]
Voltage	DC24V
Power	14W/M [4.3W/ft.]
CCT/Wavelength	2700K±120K 3000K±150K 3500K±300K 4000K±300K 5000K±400K 6000K±500K (LED is 3-step SDCM in one bin)
Brightness @4000K&CRI80	970lm/M [296lm/ft.]
Light Efficiency @4000K&CRI80	69lm/W

Brightness @4000K&CRI90	830lm/M [253lm/ft.]
Light Efficiency @4000K&CRI90	59lm/W
Beam Angle	120°
IP&IK Rating	IP67 [Wet] & IK06

Request pricing & availability

Request a product quote at truled.com

Include any configuration reference, quantities, required lengths and project location.

A configuration reference identifies a published specification row. A row may list multiple options; it is not confirmation that every option is included. This sheet is not an installation instruction or an approved project submittal.