DUAL-BEND NEON FLEX

# Wildlife Friendly Turtle-Safe · Dual-Bend neon flex

**TRU-NDM24V**

Wildlife Friendly Turtle-Safe · Dual-Bend neon flex. Review the dimensions and electrical ratings for your installation.

Use this catalog sheet to discuss your project. Final dimensions, ratings, certifications and available configurations must be confirmed for the selected product.



## Product specifications

| | |
|---|---|
| Truled part number | TRU-NDM24V |
| Category | Neon flex |
| Product type | Dual-bend neon flex |

## Configuration reference

### TRU-NDM24V-A

| | |
|---|---|
| Style | Dual-Bend (Yellow/ Amber) |
| Dimension | W16xH16mm [W0.63xH0.63in.] |
| Max. Run Length & Max. Shipping Length | 5M [16.4ft.] & 50M [164ft.] |
| Increment | 50mm [1.97in.] |
| LED Type | SMD 2835 |
| LED Qty | 120LED/M [36LED/ft.] |
| Voltage | DC24V |
| Power | 14W/M [4.27W/ft.] |
| CCT / Wavelength | 585-595nm |
| Brightness | 150lm/M [46lm/ft.] |
| Light Efficiency | 11lm/W |
| Beam Angle | 120° |
| IP&IK Rating | IP67 [Wet] & IK06 |

## Configuration reference

### TRU-NDM24V-B

| | |
|---|---|
| Style | Dual-Bend (Orange) |
| Dimension | W16xH16mm [W0.63xH0.63in.] |
| Max. Run Length & Max. Shipping Length | 5M [16.4ft.] & 50M [164ft.] |
| Increment | 50mm [1.97in.] |
| LED Type | SMD 2835 |
| LED Qty | 120LED/M [36LED/ft.] |
| Voltage | DC24V |
| Power | 14W/M [4.27W/ft.] |
| CCT / Wavelength | 600-605nm |
| Brightness | 250lm/M [76lm/ft.] |
| Light Efficiency | 18lm/W |
| Beam Angle | 120° |
| IP&IK Rating | IP67 [Wet] & IK06 |

## Configuration reference

### TRU-NDM24V-C

| | |
|---|---|
| Style | Dual-Bend (Red) |
| Dimension | W16xH16mm [W0.63xH0.63in.] |
| Max. Run Length & Max. Shipping Length | 5M [16.4ft.] & 50M [164ft.] |
| Increment | 50mm [1.97in.] |
| LED Type | SMD 2835 |
| LED Qty | 120LED/M [36LED/ft.] |
| Voltage | DC24V |
| Power | 14W/M [4.27W/ft.] |
| CCT / Wavelength | 615-625nm |
| Brightness | 320lm/M [98lm/ft.] |
| Light Efficiency | 23lm/W |
| Beam Angle | 120° |
| IP&IK Rating | IP67 [Wet] & IK06 |

## Request pricing & availability

Request a product quote at truled.com

Include any configuration reference, quantities, required lengths and project location.

A configuration reference identifies a published specification row. A row may list multiple options; it is not confirmation that every option is included. This sheet is not an installation instruction or an approved project submittal.