
HIGH-TEMPERATURE NEON FLEX

100°C · Top-Bend & Side-Bend neon flex

TRU-NH24V

100°C · Top-Bend & Side-Bend neon flex. Review the dimensions and electrical ratings for your installation.

Use this catalog sheet to discuss your project. Final dimensions, ratings, certifications and available configurations must be confirmed for the selected product.



Product specifications

Truled part number	TRU-NH24V
Category	Neon flex
Product type	High-temperature neon flex

Configuration reference

TRU-NH24V-A

Style	Top-Bend (White)
Dimension	W20*H20mm [W0.79*H0.79in]
Increment	50mm [1.97in.]
LED Type	SMD2835
LED Qty	120LED/M [36LED/ft.]
Voltage	24VDC
Power	9.6W/M [2.93W/ft.]
CCT / Wavelength	2700K 3000K 3500K 4000K 5000K 6500K
Brightness @4000K&CRI90	550lm/M [168lm/ft.]
Light Efficiency @4000K&CRI90	57lm/W
Beam Angle	120°
IP&IK Rating	IP67 [Wet] & IK07

Configuration reference

TRU-NH24V-B

Style	Side-Bend (White)
Dimension	W10*H20mm [W0.39*H0.79in]
Increment	50mm [1.97in.]
LED Type	SMD2835
LED Qty	120LED/M [36LED/ft.]
Voltage	24VDC
Power	9.6W/M [2.93W/ft.]
CCT / Wavelength	2700K 3000K 3500K 4000K 5000K 6500K
Brightness @4000K&CRI90	320lm/M [98lm/ft.]
Light Efficiency @4000K&CRI90	33lm/W
Beam Angle	120°
IP&IK Rating	IP67 [Wet] & IK07

Request pricing & availability

Request a product quote at truled.com

Include any configuration reference, quantities, required lengths and project location.

A configuration reference identifies a published specification row. A row may list multiple options; it is not confirmation that every option is included. This sheet is not an installation instruction or an approved project submittal.