RIGID NEON PROFILES

External Corner-Mounting Non-Bendable neon flex

TRU-NR24V

External Corner-Mounting Non-Bendable neon flex. Review the dimensions and electrical ratings for your installation.

Use this catalog sheet to discuss your project. Final dimensions, ratings, certifications and available configurations must be confirmed for the selected product.



Product specifications

Truled part number	TRU-NR24V
Category	Neon flex
Product type	Rigid neon profiles

Configuration reference

TRU-NR24V-A

Style	Non-Bendable (White)
Dimension	W33xH33mm [W1.3xH1.3in.]
Max. Run Length & Max. Shipping Length	3M [9.84ft.] & 3M [9.84ft.]
Increment	Free-cutting to be any length
LED Type	SMD 2835
LED Qty	120LED/M [36LED/ft.]
Voltage	DC24V
Power	14W/M [4.27W/ft.]
CCT / Wavelength	2700K±120K 3000K±150K 3500K±300K 4000K±300K 5000K±400K 6000K±500K (LED is 3-step SDCM in one bin)
Brightness @4000K&CRI80	741lm/M [226lm/ft.]
Light Efficiency @4000K&CRI80	53lm/W
Brightness @4000K&CRI90	630lm/M [192lm/ft.]
Light Efficiency @4000K&CRI90	45lm/W
Beam Angle	120°
IP&IK Rating	IP65[wet] & IK09

Configuration reference

TRU-NR24V-B

Style	Non-Bendable (CCT)
Dimension	W33xH33mm [W1.3xH1.3in.]
Max. Run Length & Max. Shipping Length	3M [9.84ft.] & 3M [9.84ft.]
Increment	50mm [1.97in.]
LED Type	SMD 2835
LED Qty	240LED/M [73LED/ft.]
Voltage	DC24V
Power	14W/M [4.27W/ft.]
CCT / Wavelength	2700-6000K CCT-Tunable (LED is 3-step SDCM in one bin)
Brightness @4000K&CRI80	Not specified
Light Efficiency @4000K&CRI80	Not specified
Brightness @4000K&CRI90	630lm/M [192lm/ft.]
Light Efficiency @4000K&CRI90	45lm/W
Beam Angle	120°
IP&IK Rating	IP65[wet] & IK09

Configuration reference

TRU-NR24V-C

Style	Non-Bendable (RGB)
Dimension	W33xH33mm [W1.3xH1.3in.]
Max. Run Length & Max. Shipping Length	3M [9.84ft.] & 3M [9.84ft.]
Increment	50mm [1.97in.]
LED Type	SMD 4040
LED Qty	120LED/M [36LED/ft.]
Voltage	DC24V
Power	14W/M [4.27W/ft.]
CCT / Wavelength	R:620-630nm G:515-530nm B:460-470nm
Brightness @4000K&CRI80	300lm/M [91lm/ft.]
Light Efficiency @4000K&CRI80	21lm/W
Brightness @4000K&CRI90	Not specified
Light Efficiency @4000K&CRI90	Not specified
Beam Angle	120°
IP&IK Rating	IP65[wet] & IK09

Configuration reference

TRU-NR24V-D

Style	Non-Bendable (RGBW)
Dimension	W33xH33mm [W1.3xH1.3in.]
Max. Run Length & Max. Shipping Length	3M [9.84ft.] & 3M [9.84ft.]
Increment	50mm [1.97in.]
LED Type	SMD 4040
LED Qty	120LED/M [36LED/ft.]
Voltage	DC24V
Power	14W/M [4.27W/ft.]
CCT / Wavelength	R:620-630nm G:515-530nm B:460-470nm W:2700-6000K (W: LED is 5-step SDCM in one bin)
Brightness @4000K&CRI80	Not specified
Light Efficiency @4000K&CRI80	Not specified
Brightness @4000K&CRI90	320lm/M [98lm/ft.]
Light Efficiency @4000K&CRI90	23lm/W
Beam Angle	120°
IP&IK Rating	IP65[wet] & IK09

Request pricing & availability

Request a product quote at truled.com

Include any configuration reference, quantities, required lengths and project location.

A configuration reference identifies a published specification row. A row may list multiple options; it is not confirmation that every option is included. This sheet is not an installation instruction or an approved project submittal.