SIDE-BEND NEON FLEX

Ultra-Long · Top-Bend & Side-Bend neon flex

TRU-NSA

Ultra-Long · Top-Bend & Side-Bend neon flex. Review the dimensions and electrical ratings for your installation.

Use this catalog sheet to discuss your project. Final dimensions, ratings, certifications and available configurations must be confirmed for the selected product.



Product specifications

Truled part number	TRU-NSA
Category	Neon flex
Product type	Side-bend neon flex

Configuration reference

TRU-NSA-A

Style	Top-Bend (White Ultra-Long)
Dimension	W16xH16mm [W0.63xH0.63in.]
Max. Run Length & Max. Shipping Length	20/30/50)M [(65.6/98.4/164)ft.] & 50M [164ft.]
Increment	50mm [1.97in.]
LED Type	SMD 2835
LED Qty	120LED/M [36LED/ft.]
Voltage	DC24V
Power	14/9.6/4.8)W/M [(4.27/2.93/1.46)W/ft.]
CCT / Wavelength	2700K±120K 3000K±150K 3500K±300K 4000K±300K 5000K±400K 6000K±500K
Brightness @4000K&CRI80	940/640/320)lm/M [(287/195/98)lm/ft.]
Light Efficacy @4000K&CRI80	67lm/W
Brightness @4000K&CRI90	800/550/270)lm/M [(244/168/82)lm/ft.]
Light Efficacy @4000K&CRI90	57lm/W
Beam Angle	120°
IP&IK Rating	IP67/IP68 [Wet] & IK08

Configuration reference

TRU-NSA-B

Style	Top-Bend (White Ultra-Long)
Dimension	W16xH16mm [W0.63xH0.63in.]
Max. Run Length & Max. Shipping Length	35/50)M [(115/164)ft.] & 50M [164ft.]
Increment	100mm [3.94in.]
LED Type	SMD 2835
LED Qty	120LED/M [36LED/ft.]
Voltage	DC48V
Power	14/9.6)W/M [(4.27/2.93)W/ft.]
CCT / Wavelength	2700K±120K 3000K±150K 3500K±300K 4000K±300K 5000K±400K 6000K±500K
Brightness @4000K&CRI80	940/640)lm/M [(287/195)lm/ft.]
Light Efficacy @4000K&CRI80	67lm/W
Brightness @4000K&CRI90	800/550/270)lm/M [(244/168/82)lm/ft.]
Light Efficacy @4000K&CRI90	57lm/W
Beam Angle	120°
IP&IK Rating	IP67/IP68 [Wet] & IK08

Configuration reference

TRU-NSA-C

Style	Side-Bend (White Ultra-Long)
Dimension	W11.5xH20mm [W0.45xH0.79in.]
Max. Run Length & Max. Shipping Length	20/30/50)M [(65.6/98.4/164)ft.] & 50M [164ft.]
Increment	50mm [1.97in.]
LED Type	SMD 2835
LED Qty	120LED/M [36LED/ft.]
Voltage	DC24V
Power	14/9.6/4.8)W/M [(4.27/2.93/1.46)W/ft.]
CCT / Wavelength	2700K±120K 3000K±150K 3500K±300K 4000K±300K 5000K±400K 6000K±500K
Brightness @4000K&CRI80	670/460/230)lm/M [(204/140/70)lm/ft.]
Light Efficacy @4000K&CRI80	48lm/W
Brightness @4000K&CRI90	570/390/200)lm/M [(174/119/61)lm/ft.]
Light Efficacy @4000K&CRI90	41lm/W
Beam Angle	120°
IP&IK Rating	IP67/IP68 [Wet] & IK08

Configuration reference

TRU-NSA-D

Style	Side-Bend (White Ultra-Long)
Dimension	W11.5xH20mm [W0.45xH0.79in.]
Max. Run Length & Max. Shipping Length	35/50)M [(115/164)ft.] & 50M [164ft.]
Increment	100mm [3.94in.]
LED Type	SMD 2835
LED Qty	120LED/M [36LED/ft.]
Voltage	DC48V
Power	14/9.6)W/M [(4.27/2.93)W/ft.]
CCT / Wavelength	2700K±120K 3000K±150K 3500K±300K 4000K±300K 5000K±400K 6000K±500K
Brightness @4000K&CRI80	670/460)lm/M [(204/140)lm/ft.]
Light Efficacy @4000K&CRI80	48lm/W
Brightness @4000K&CRI90	570/390)lm/M [(174/119)lm/ft.]
Light Efficacy @4000K&CRI90	41lm/W
Beam Angle	120°
IP&IK Rating	IP67/IP68 [Wet] & IK08

Request pricing & availability

Request a product quote at truled.com

Include any configuration reference, quantities, required lengths and project location.

A configuration reference identifies a published specification row. A row may list multiple options; it is not confirmation that every option is included. This sheet is not an installation instruction or an approved project submittal.