
SIDE-BEND NEON FLEX

Top-Bend & Side-Bend neon flex

TRU-NSB24V

Top-Bend & Side-Bend neon flex. Review the dimensions and electrical ratings for your installation.

Use this catalog sheet to discuss your project. Final dimensions, ratings, certifications and available configurations must be confirmed for the selected product.



Product specifications

Truled part number	TRU-NSB24V
Category	Neon flex
Product type	Side-bend neon flex
Style	Side-Bend (White)
Dimension	W10*H10mm [W0.39*H0.39in.]
Max. Run Length & Max. Shipping Length	5M [16.4ft.] & 50M [164ft.]
Increment	Free-cutting to be any length
LED Type	Not specified
LED Qty	180LED/M (54LED/ft.)
Voltage	DC24V
Power	9W/M [2.74W/ft.]
CCT/Wavelength	2700K±120K 3000K±150K 3500K±300K 4000K±300K 5000K±400K 6000K±500K
Brightness @4000K&CRI80	690lm/M [210lm/ft.]
Light Efficiency @4000K&CRI80	76lm/W

Brightness @4000K&CRI90	590lm/M [180lm/ft.]
Light Efficiency @4000K&CRI90	65lm/W
Beam Angle	120°
IP&IK Rating	IP67/IP68 (Wet) & IK06

Configuration reference

TRU-NSB24V-A

Style	Top-Bend (White)
Dimension	W10*H10mm [W0.39*H0.39in.]
Max. Run Length & Max. Shipping Length	5M [16.4ft.] & 50M [164ft.]
Increment	Free-cutting to be any length
LED Type	Not specified
LED Qty	180LED/M (54LED/ft.)
Voltage	DC24V
Power	9W/M [2.74W/ft.]
CCT/Wavelength	2700K±120K 3000K±150K 3500K±300K 4000K±300K 5000K±400K 6000K±500K
Brightness @4000K&CRI80	790lm/M [241lm/ft.]
Light Efficiency @4000K&CRI80	88lm/W
Brightness @4000K&CRI90	675lm/M [206lm/ft.]
Light Efficiency @4000K&CRI90	75lm/W
Beam Angle	120°
IP&IK Rating	IP67/IP68 (Wet) & IK06

Configuration reference

TRU-NSB24V-B

Style	Top-Bend (White)
Dimension	W10*H10mm [W0.39*H0.39in.]
Max. Run Length & Max. Shipping Length	5M [16.4ft.] & 50M [164ft.]
Increment	Free-cutting to be any length
LED Type	Not specified
LED Qty	180LED/M (54LED/ft.)
Voltage	DC24V
Power	*8W/M *[2.44W/ft.]
CCT/Wavelength	2700K±120K 3000K±150K 3500K±300K 4000K±300K 5000K±400K 6000K±500K
Brightness @4000K&CRI80	*690lm/M *[210lm/ft.]
Light Efficiency @4000K&CRI80	86lm/W
Brightness @4000K&CRI90	*590lm/M *[180lm/ft.]
Light Efficiency @4000K&CRI90	74lm/W
Beam Angle	120°
IP&IK Rating	IP67/IP68 (Wet) & IK06

Request pricing & availability

Request a product quote at truled.com

Include any configuration reference, quantities, required lengths and project location.

A configuration reference identifies a published specification row. A row may list multiple options; it is not confirmation that every option is included. This sheet is not an installation instruction or an approved project submittal.