SIDE-BEND NEON FLEX

Side-Bend neon flex

TRU-NSF24V

Side-Bend neon flex. Review the dimensions and electrical ratings for your installation.

Use this catalog sheet to discuss your project. Final dimensions, ratings, certifications and available configurations must be confirmed for the selected product.



Product specifications

Truled part number	TRU-NSF24V
Category	Neon flex
Product type	Side-bend neon flex
Style	Side-Bend (Colorful Jacket)
Dimension	W7xH15mm [W0.28xH0.59in.]
Max. Run Length & Max. Shipping Length	10M [32.8ft.] & 50M [164ft.]
Increment	Free-cutting to be any length
LED Type	SMD 2835
LED Qty	160LED/M [49LED/ft.]
Voltage	DC24V
Power	9W/M [2.74W/ft.]
CCT / Wavelength	White Red Green Blue Yellow Orange Purple
Brightness @4000K&CRI80	White: 252lm/M [77lm/ft.] Red: 54lm/M [16lm/ft.] Green: 22lm/M [7lm/ft.] Blue: 7lm/M [2lm/ft.] Yellow: 216lm/M [66lm/ft.] Orange: 99lm/M [30lm/ft.] Purple: 32lm/M [10lm/ft.]

Light Efficacy @4000K&CRI80	White: 28lm/W Red: 6lm/W Green: 2.4lm/W Blue: 0.8lm/W Yellow: 24lm/W Orange: 11lm/W Purple: 3.5lm/W
Brightness @4000K&CRI90	White: 220lm/M [67lm/ft.] Red: 43lm/M [13lm/ft.] Green: 21lm/M [6lm/ft.] Blue: 6lm/M [2lm/ft.] Yellow: 180lm/M [55lm/ft.] Orange: 77lm/M [23lm/ft.] Purple: 26lm/M [8lm/ft.]
Light Efficacy @4000K&CRI90	White: 24lm/W Red: 5lm/W Green: 2lm/W Blue: 0.7lm/W Yellow: 20lm/W Orange: 9lm/W Purple: 3lm/W
Beam Angle	120°
IP&IK Rating	IP67 [Wet] & IK06

Request pricing & availability

Request a product quote at truled.com

Include any configuration reference, quantities, required lengths and project location.

A configuration reference identifies a published specification row. A row may list multiple options; it is not confirmation that every option is included. This sheet is not an installation instruction or an approved project submittal.