SIDE-BEND NEON FLEX

65°C · Top-Bend & Side-Bend neon flex

TRU-NSH24V

65°C · Top-Bend & Side-Bend neon flex. Review the dimensions and electrical ratings for your installation.

Use this catalog sheet to discuss your project. Final dimensions, ratings, certifications and available configurations must be confirmed for the selected product.



Product specifications

Truled part number	TRU-NSH24V
Category	Neon flex
Product type	Side-bend neon flex

Configuration reference

TRU-NSH24V-A

Style	Top-Bend (White All-Weather)
Dimension	W16xH16mm [W0.63xH0.63in.]
Max. Run Length & Max. Shipping Length	10/15/20)M [(32.8/49.2/65.6)ft.] & 50M [164ft.]
Increment	50mm [1.97in.]
LED Type	SMD 2835
LED Qty	160LED/M [49LED/ft.]
Voltage	DC24V
Power	14/9.6/4.8)W/M [(4.27/2.93/1.46)W/ft.]
CCT / Wavelength	2700K±120K 3000K±150K 3500K±300K 4000K±300K 5000K±400K 6000K±500K
Brightness @4000K&CRI90	1050/720/360)lm/M [(320/220/110)lm/ft.]
Light Efficacy @4000K&CRI90	75lm/W
Beam Angle	120°
IP&IK Rating	IP67/IP68 [Wet] & IK08
Operation Ambient	20~65°C [-4~149°F]

Configuration reference

TRU-NSH24V-B

Style	Side-Bend (White All-Weather)
Dimension	W11.5xH20mm [W0.45xH0.79in.]
Max. Run Length & Max. Shipping Length	10/15/20)M [(32.8/49.2/65.6)ft.] & 50M [164ft.]
Increment	50mm [1.97in.]
LED Type	SMD 2835
LED Qty	160LED/M [49LED/ft.]
Voltage	DC24V
Power	14/9.6/4.8)W/M [(4.27/2.93/1.46)W/ft.]
CCT / Wavelength	2700K±120K 3000K±150K 3500K±300K 4000K±300K 5000K±400K 6000K±500K
Brightness @4000K&CRI90	770/528/264)lm/M [(235/161/80)lm/ft.]
Light Efficacy @4000K&CRI90	55lm/W
Beam Angle	120°
IP&IK Rating	IP67/IP68 [Wet] & IK08
Operation Ambient	20~65°C [-4~149°F]

Request pricing & availability

Request a product quote at truled.com

Include any configuration reference, quantities, required lengths and project location.

A configuration reference identifies a published specification row. A row may list multiple options; it is not confirmation that every option is included. This sheet is not an installation instruction or an approved project submittal.