SIDE-BEND NEON FLEX

Wall-Mounting · Side-Bend neon flex

TRU-NSJ24V

Wall-Mounting · Side-Bend neon flex. Review the dimensions and electrical ratings for your installation.

Use this catalog sheet to discuss your project. Final dimensions, ratings, certifications and available configurations must be confirmed for the selected product.



Product specifications

Truled part number	TRU-NSJ24V
Category	Neon flex
Product type	Side-bend neon flex

Configuration reference

TRU-NSJ24V-A

Style	Side-Bend (White)
Dimension	W20xH14mm [W0.79xH0.55in.]
Max. Run Length & Max. Shipping Length	5M [16.4ft.] (Power fed on one side) & 50M [164ft.]
Increment	Free-cutting to be any length
LED Type	SMD 2835
LED Qty	120LED/M [36LED/ft.]
Voltage	DC24V
Power	14W/M [4.27W/ft.]
CCT / Wavelength	2700K±120K 3000K±150K 3500K±300K 4000K±300K 5000K±400K 6000K±500K (LED is 3-step SDCM in one bin)
Brightness @4000K&CRI80	Not specified
Light Efficiency @4000K&CRI80	Not specified
Brightness @4000K&CRI90	700lm/M [213lm/ft.]
Light Efficiency @4000K&CRI90	50lm/W
Beam Angle	120°
IP&IK Rating	IP67[wet] (die-casting process) & IP20 (gluing process) [dry] & IK07

Configuration reference

TRU-NSJ24V-B

Style	Side-Bend (CCT)
Dimension	W20xH14mm [W0.79xH0.55in.]
Max. Run Length & Max. Shipping Length	5M [16.4ft.] (Power fed on one side) & 50M [164ft.]
Increment	Free-cutting to be any length
LED Type	SMD 2835
LED Qty	240LED/M [73LED/ft.]
Voltage	DC24V
Power	14W/M [4.27W/ft.]
CCT / Wavelength	2700-6000K CCT-Tunable (LED is 3-step SDCM in one bin)
Brightness @4000K&CRI80	Not specified
Light Efficiency @4000K&CRI80	Not specified
Brightness @4000K&CRI90	860lm/M [262lm/ft.]
Light Efficiency @4000K&CRI90	61lm/W
Beam Angle	120°
IP&IK Rating	IP67[wet] (die-casting process) & IP20 (gluing process) [dry] & IK07

Configuration reference

TRU-NSJ24V-C

Style	Side-Bend (RGB)
Dimension	W20xH14mm [W0.79xH0.55in.]
Max. Run Length & Max. Shipping Length	5M [16.4ft.] (Power fed on one side) & 50M [164ft.]
Increment	50mm [1.97in.]
LED Type	SMD 4040
LED Qty	120LED/M [36LED/ft.]
Voltage	DC24V
Power	14W/M [4.27W/ft.]
CCT / Wavelength	R:620-630nm G:515-530nm B:460-470nm
Brightness @4000K&CRI80	340lm/M [104lm/ft.]
Light Efficiency @4000K&CRI80	24lm/W
Brightness @4000K&CRI90	Not specified
Light Efficiency @4000K&CRI90	Not specified
Beam Angle	120°
IP&IK Rating	IP67[wet] (die-casting process) & IP20 (gluing process) [dry] & IK07

Configuration reference

TRU-NSJ24V-D

Style	Side-Bend (RGBW)
Dimension	W20xH14mm [W0.79xH0.55in.]
Max. Run Length & Max. Shipping Length	5M [16.4ft.] (Power fed on one side) & 50M [164ft.]
Increment	50mm [1.97in.]
LED Type	SMD 4040
LED Qty	120LED/M [36LED/ft.]
Voltage	DC24V
Power	14W/M [4.27W/ft.]
CCT / Wavelength	R:620-630nm G:515-530nm B:460-470nm W:2700-6000K
Brightness @4000K&CRI80	Not specified
Light Efficiency @4000K&CRI80	Not specified
Brightness @4000K&CRI90	410lm/M [125lm/ft.]
Light Efficiency @4000K&CRI90	29lm/W
Beam Angle	120°
IP&IK Rating	IP67[wet] (die-casting process) & IP20 (gluing process) [dry] & IK07

Request pricing & availability

Request a product quote at truled.com

Include any configuration reference, quantities, required lengths and project location.

A configuration reference identifies a published specification row. A row may list multiple options; it is not confirmation that every option is included. This sheet is not an installation instruction or an approved project submittal.