TOP-BEND NEON FLEX

Top-Bend & neon flex

TRU-NTD24V

Top-Bend & neon flex. Review the dimensions and electrical ratings for your installation.

Use this catalog sheet to discuss your project. Final dimensions, ratings, certifications and available configurations must be confirmed for the selected product.



Product specifications

Truled part number	TRU-NTD24V
Category	Neon flex
Product type	Top-bend neon flex

Configuration reference

TRU-NTD24V-A

Style	Top-Bend (White) 3-Sided Black Jacket
Dimension	W10xH10mm [W0.39xH0.39in.]
Max. Run Length & Max. Shipping Length	5M [16.4ft.] & 50M [164ft.]
Increment	Free-cutting to be any length
LED Type	SMD2835
LED Qty	196LED/M [60LED/ft.]
Voltage	DC24V
Power	8W/M [2.44W/ft.]
CCT/Wavelength	2700K±120K 3000K±150K 3500K±300K 4000K±300K 5000K±400K 6000K±500K
Brightness @4000K&CRI80	570lm/M [174lm/ft.]
Light Efficiency @4000K&CRI80	71lm/W
Brightness @4000K&CRI90	480lm/M [146lm/ft.]
Light Efficiency @4000K&CRI90	60lm/W
Beam Angle	120°
IP&IK Rating	IP67 [Wet] & IK06

Published options

Published specification row 2

Style	Not specified
Dimension	W10xH10mm [W0.39xH0.39in.]
Max. Run Length & Max. Shipping Length	Not specified
Increment	Not specified
LED Type	Not specified
LED Qty	Not specified
Voltage	DC24V
Power	Not specified
CCT/Wavelength	Not specified
Brightness @4000K&CRI80	Not specified
Light Efficiency @4000K&CRI80	Not specified
Brightness @4000K&CRI90	Not specified
Light Efficiency @4000K&CRI90	Not specified
Beam Angle	Not specified
IP&IK Rating	IP67 [Wet] & IK06

Configuration reference

TRU-NTD24V-B

Style	Top-Bend (White) 4-Sided Black Jacket
Dimension	W10xH10mm [W0.39xH0.39in.]
Max. Run Length & Max. Shipping Length	5M [16.4ft.] & 50M [164ft.]
Increment	Free-cutting to be any length
LED Type	SMD2835
LED Qty	196LED/M [60LED/ft.]
Voltage	DC24V
Power	8W/M [2.44W/ft.]
CCT/Wavelength	2700K±150K 3000K±200K 4000K±350K
Brightness @4000K&CRI80	104lm/M [32lm/ft.]
Light Efficiency @4000K&CRI80	13lm/W
Brightness @4000K&CRI90	88lm/M [27lm/ft.]
Light Efficiency @4000K&CRI90	11lm/W
Beam Angle	90°
IP&IK Rating	IP67 [Wet] & IK06

Request pricing & availability

Request a product quote at truled.com

Include any configuration reference, quantities, required lengths and project location.

A configuration reference identifies a published specification row. A row may list multiple options; it is not confirmation that every option is included. This sheet is not an installation instruction or an approved project submittal.