TOP-BEND NEON FLEX

Asymmetric Surface-Mounting · Top-Bend neon flex

TRU-NTE24V

Asymmetric Surface-Mounting · Top-Bend neon flex. Review the dimensions and electrical ratings for your installation.

Use this catalog sheet to discuss your project. Final dimensions, ratings, certifications and available configurations must be confirmed for the selected product.



Product specifications

Truled part number	TRU-NTE24V
Category	Neon flex
Product type	Top-bend neon flex

Configuration reference

TRU-NTE24V-A

Style	Top-Bend (White) White Jacket
Dimension	W14.4*H6mm [W0.57*H0.24in.]
Max. Run Length & Max. Shipping Length	5M [16.4ft.] & 50M [164ft.]
Increment	Free-cutting to be any length
LED Type	SMD 2216
LED Qty	300LED/M [91LED/ft.]
Voltage	DC24V
Power	12W/M [3.66W/ft.]
Finished Product CCT/ Wavelength	2700K±120K 3000K±150K 3500K±300K 4000K±300K 5000K±400K 6000K±500K
Brightness @4000K&CRI90	840lm/M [256lm/ft.]
Light Efficiency @4000K&CRI90	70lm/W
Beam Angle	120° (asymmetric 30°)
IP&IK Rating	IP54 [Wet] (For indoor use only) & IK04

Configuration reference

TRU-NTE24V-B

Style	Top-Bend (White) Black Jacket
Dimension	W14.4*H6mm [W0.57*H0.24in.]
Max. Run Length & Max. Shipping Length	5M [16.4ft.] & 50M [164ft.]
Increment	Free-cutting to be any length
LED Type	SMD 2216
LED Qty	300LED/M [91LED/ft.]
Voltage	DC24V
Power	12W/M [3.66W/ft.]
Finished Product CCT/ Wavelength	2700K±120K 3000K±150K 3500K±300K 4000K±300K 5000K±400K 6000K±500K
Brightness @4000K&CRI90	780lm/M [238lm/ft.]
Light Efficiency @4000K&CRI90	65lm/W
Beam Angle	120° (asymmetric 30°)
IP&IK Rating	IP54 [Wet] (For indoor use only) & IK04

Request pricing & availability

Request a product quote at truled.com

Include any configuration reference, quantities, required lengths and project location.

A configuration reference identifies a published specification row. A row may list multiple options; it is not confirmation that every option is included. This sheet is not an installation instruction or an approved project submittal.