TOP-BEND NEON FLEX

Medium Corner-Mounting · Top-Bend neon flex

TRU-NTI24V

Medium Corner-Mounting · Top-Bend neon flex. Review the dimensions and electrical ratings for your installation.

Use this catalog sheet to discuss your project. Final dimensions, ratings, certifications and available configurations must be confirmed for the selected product.



Product specifications

Truled part number	TRU-NTI24V
Category	Neon flex
Product type	Top-bend neon flex

Configuration reference

TRU-NTI24V-A

Style	Top-Bend (White)
Dimension	W16xH16mm [W0.63xH0.63in.]
Max. Run Length & Max. Shipping Length	5M [16.4ft.] (Power fed on one side) & 50M [164ft.]
Increment	Free-cutting to be any length
LED Type	SMD 2835
LED Qty	196LED/M [60LED/ft.]
Voltage	DC24V
Power	12W/M [3.7W/ft.]
CCT / Wavelength	2700K±120K 3000K±150K 3500K±300K 4000K±300K 5000K±400K 6000K±500K (LED is 3-step SDCM in one bin)
Brightness @4000K&CRI80	Not specified
Light Efficiency @4000K&CRI80	Not specified
Brightness @4000K&CRI90	960lm/M [293lm/ft.]
Light Efficiency @4000K&CRI90	80lm/W
Beam Angle	120°
IP&IK Rating	IP67[wet] (die-casting process) & IP20 (gluing process) [dry] & IK07

Configuration reference

TRU-NTI24V-B

Style	Top-Bend (CCT)
Dimension	W16xH16mm [W0.63xH0.63in.]
Max. Run Length & Max. Shipping Length	5M [16.4ft.] (Power fed on one side) & 50M [164ft.]
Increment	35.7mm [1.4in.]
LED Type	SMD 2216
LED Qty	392LED/M [120LED/ft.]
Voltage	DC24V
Power	12W/M [3.7W/ft.]
CCT / Wavelength	2700-6000K CCT-Tunable (LED is 3-step SDCM in one bin)
Brightness @4000K&CRI80	Not specified
Light Efficiency @4000K&CRI80	Not specified
Brightness @4000K&CRI90	1040lm/M [317lm/ft.]
Light Efficiency @4000K&CRI90	87lm/W
Beam Angle	120°
IP&IK Rating	IP67[wet] (die-casting process) & IP20 (gluing process) [dry] & IK07

Configuration reference

TRU-NTI24V-C

Style	Top-Bend (RGB)
Dimension	W16xH16mm [W0.63xH0.63in.]
Max. Run Length & Max. Shipping Length	5M [16.4ft.] (Power fed on one side) & 50M [164ft.]
Increment	35.7mm [1.4in.]
LED Type	SMD 2835
LED Qty	168LED/M [51LED/ft.]
Voltage	DC24V
Power	12W/M [3.7W/ft.]
CCT / Wavelength	R: 615-625nm G: 515-530nm B: 460-470nm
Brightness @4000K&CRI80	470lm/M [143lm/ft.]
Light Efficiency @4000K&CRI80	39lm/W
Brightness @4000K&CRI90	Not specified
Light Efficiency @4000K&CRI90	Not specified
Beam Angle	120°
IP&IK Rating	IP67[wet] (die-casting process) & IP20 (gluing process) [dry] & IK07

Configuration reference

TRU-NTI24V-D

Style	Top-Bend (SPI RGB)
Dimension	W16xH16mm [W0.63xH0.63in.]
Max. Run Length & Max. Shipping Length	5M [16.4ft.] (Power fed on one side) & 50M [164ft.]
Increment	50mm [1.97in.]
LED Type	SMD 2835
LED Qty	120LED/M [36LED/ft.]
Voltage	DC24V
Power	14W/M [4.27W/ft.].
CCT / Wavelength	R: 615-625nm G: 515-530nm B: 460-470nm
Brightness @4000K&CRI80	380lm/M [116lm/ft.]
Light Efficiency @4000K&CRI80	27lm/W
Brightness @4000K&CRI90	Not specified
Light Efficiency @4000K&CRI90	Not specified
Beam Angle	120°
IP&IK Rating	IP67[wet] (die-casting process) & IP20 (gluing process) [dry] & IK07

Request pricing & availability

Request a product quote at truled.com

Include any configuration reference, quantities, required lengths and project location.

A configuration reference identifies a published specification row. A row may list multiple options; it is not confirmation that every option is included. This sheet is not an installation instruction or an approved project submittal.