TOP-BEND NEON FLEX

Top-Bend neon flex

TRU-NTK24V

Top-Bend neon flex. Review the dimensions and electrical ratings for your installation.

Use this catalog sheet to discuss your project. Final dimensions, ratings, certifications and available configurations must be confirmed for the selected product.



Product specifications

Truled part number	TRU-NTK24V
Category	Neon flex
Product type	Top-bend neon flex

Configuration reference

TRU-NTK24V-A

Style	Top-Bend (White)
Dimension	W10*H10mm [W0.39*H0.39in.]
Max. Run Length & Max. Shipping Length	5M [16.4ft.] & 50M [164ft.]
Increment	Free-cutting to be any length
LED Qty	196LED/M [60LED/ft.]
Voltage	24VDC
Power	12W/M [3.66W/ft.]
CCT / Wavelength	2700K±120K 3000K±150K 3500K±300K 4000K±300K 5000K±400K 6000K±500K (LED is 3-step SDCM in one bin)
Brightness @4000K&CRI80	Not specified
Light Efficacy @4000K&CRI80	Not specified
Brightness @4000K&CRI90	880lm/M [268lm/ft.]
Light Efficacy @4000K&CRI90	73lm/W
Beam Angle	120°
IP&IK Rating	IP67 [Wet] & IK06

Configuration reference

TRU-NTK24V-B

Style	Top-Bend (CCT)
Dimension	W10*H10mm [W0.39*H0.39in.]
Max. Run Length & Max. Shipping Length	5M [16.4ft.] & 50M [164ft.]
Increment	35.7mm [1.41in.]
LED Qty	392LED/M [120LED/ft.]
Voltage	24VDC
Power	12W/M [3.66W/ft.]
CCT / Wavelength	2700-6500K CCT-Tunable (LED is 3-step SDCM in one bin)
Brightness @4000K&CRI80	Not specified
Light Efficacy @4000K&CRI80	Not specified
Brightness @4000K&CRI90	950lm/M [290lm/ft.]
Light Efficacy @4000K&CRI90	79lm/W
Beam Angle	120°
IP&IK Rating	IP67 [Wet] & IK06

Configuration reference

TRU-NTK24V-C

Style	Top-Bend (RGB)
Dimension	W10*H10mm [W0.39*H0.39in.]
Max. Run Length & Max. Shipping Length	5M [16.4ft.] & 50M [164ft.]
Increment	35.7mm [1.41in.]
LED Qty	168LED/M [51LED/ft.]
Voltage	24VDC
Power	12W/M [3.66W/ft.]
CCT / Wavelength	R:615-625nm G:510-530nm B:460-470nm
Brightness @4000K&CRI80	400lm/M [122lm/ft.]
Light Efficacy @4000K&CRI80	33lm/W
Brightness @4000K&CRI90	Not specified
Light Efficacy @4000K&CRI90	Not specified
Beam Angle	120°
IP&IK Rating	IP67 [Wet] & IK06

Request pricing & availability

Request a product quote at truled.com

Include any configuration reference, quantities, required lengths and project location.

A configuration reference identifies a published specification row. A row may list multiple options; it is not confirmation that every option is included. This sheet is not an installation instruction or an approved project submittal.