TOP-BEND NEON FLEX

Asymmetric Recessed-Mounting Trimless · Top-Bend neon flex

TRU-NTL24V

Asymmetric Recessed-Mounting Trimless · Top-Bend neon flex. Review the dimensions and electrical ratings for your installation.

Use this catalog sheet to discuss your project. Final dimensions, ratings, certifications and available configurations must be confirmed for the selected product.



Product specifications

Truled part number	TRU-NTL24V
Category	Neon flex
Product type	Top-bend neon flex
Style	Top-Bend (White)
Dimension	W8*H4.5mm [W0.31*H0.18in.]
Max. Run Length & Max. Shipping Length	5M [16.4ft.] & 10M [32.8ft.]
Increment	Free-cutting to be any length
LED Type	SMD 2835
LED Qty	180LED/M [55LED/ft.]
Voltage	DC24V
Power	9W/M [2.74W/ft.]
Finished Product CCT/ Wavelength	2700K±120K 3000K±150K 3500K±300K 4000K±300K 5000K±400K 6000K±500K (LED is 3-step SDCM in one bin)
Brightness @4000K&CRI80	612lm/M [187lm/ft.]

Light Efficiency @4000K&CRI80	68lm/W
Brightness @4000K&CRI90	522lm/M [159lm/ft.]
Light Efficiency @4000K&CRI90	58lm/W
Beam Angle	120° (asymmetric 30°)
IP&IK Rating	IP54 [damp] (For indoor use only) & IK03

Request pricing & availability

Request a product quote at truled.com

Include any configuration reference, quantities, required lengths and project location.

A configuration reference identifies a published specification row. A row may list multiple options; it is not confirmation that every option is included. This sheet is not an installation instruction or an approved project submittal.