TOP-BEND NEON FLEX

Grille Anti-Glare Top-Bend neon flex

TRU-NTN24V

Grille Anti-Glare Top-Bend neon flex. Review the dimensions and electrical ratings for your installation.

Use this catalog sheet to discuss your project. Final dimensions, ratings, certifications and available configurations must be confirmed for the selected product.



Product specifications

Truled part number	TRU-NTN24V
Category	Neon flex
Product type	Top-bend neon flex

Configuration reference

TRU-NTN24V-A

Style	Top-Bend (White) 3-sided black
Dimension	W10xH10mm [W0.39xH0.39in.]
Max. Run Length & Max. Shipping Length	5M [16.4ft.] (Power fed on one side) & 10M [32.8ft.]
Increment	Free-cutting to be any length
LED Type	SMD2835
LED Qty	196LED/M [60LED/ft.]
Voltage	DC24V
Power	12W/M [3.66W/ft.]
CCT/Wavelength	2700K±120K 3000K±150K 3500K±300K 4000K±300K 5000K±400K 6000K±500K (LED is 3-step SDCM in one bin)
Brightness @4000K&CRI80	Not specified
Light Efficiency @4000K&CRI80	Not specified
Brightness @4000K&CRI90	156lm/M [48lm/ft.]
Light Efficiency @4000K&CRI90	13lm/W
Beam Angle	110° & 35°
IP&IK Rating	IP54 [Damp] (End cap sealed by gluing process) & IK06

Configuration reference

TRU-NTN24V-B

Style	Top-Bend (CCT) 3-sided black
Dimension	W10xH10mm [W0.39xH0.39in.]
Max. Run Length & Max. Shipping Length	5M [16.4ft.] (Power fed on one side) & 10M [32.8ft.]
Increment	35.7mm [1.4in.]
LED Type	SMD2216
LED Qty	392LED/M [120LED/ft.]
Voltage	DC24V
Power	12W/M [3.66W/ft.]
CCT/Wavelength	2700-6000K CCT-Tunable (LED is 3-step SDCM in one bin)
Brightness @4000K&CRI80	Not specified
Light Efficiency @4000K&CRI80	Not specified
Brightness @4000K&CRI90	192lm/M [59lm/ft.]
Light Efficiency @4000K&CRI90	16lm/W
Beam Angle	110° & 35°
IP&IK Rating	IP54 [Damp] (End cap sealed by gluing process) & IK06

Configuration reference

TRU-NTN24V-C

Style	Top-Bend (RGB) 3-sided black
Dimension	W10xH10mm [W0.39xH0.39in.]
Max. Run Length & Max. Shipping Length	5M [16.4ft.] (Power fed on one side) & 10M [32.8ft.]
Increment	35.7mm [1.4in.]
LED Type	SMD2835
LED Qty	168LED/M [51LED/ft.]
Voltage	DC24V
Power	12W/M [3.66W/ft.]
CCT/Wavelength	R: 615-625nm G: 515-530nm B: 460-470nm
Brightness @4000K&CRI80	60lm/M [18lm/ft.]
Light Efficiency @4000K&CRI80	5lm/W
Brightness @4000K&CRI90	Not specified
Light Efficiency @4000K&CRI90	Not specified
Beam Angle	110° & 35°
IP&IK Rating	IP54 [Damp] (End cap sealed by gluing process) & IK06

Request pricing & availability

Request a product quote at truled.com

Include any configuration reference, quantities, required lengths and project location.

A configuration reference identifies a published specification row. A row may list multiple options; it is not confirmation that every option is included. This sheet is not an installation instruction or an approved project submittal.