MULTIPLE DOWNLIGHTS

3.5” Four Head Multiple Regress Gimbal Black

TRU-RXA3P5IN4H-B

3.5” Four Head Multiple Regress Gimbal Black. Review the dimensions and electrical ratings for your installation.

Use this catalog sheet to discuss your project. Final dimensions, ratings, certifications and available configurations must be confirmed for the selected product.



Product specifications

Truled part number	TRU-RXA3P5IN4H-B
Category	Recessed lighting
Product type	Multiple downlights
Shape	Multiple
Style	Trimmed
Size	3.5 Inch
Finish	Black
Diffuser	Clear (Default)
Number of lights	4
Cutout	3.70” x 14.92”
Outside dimensions	4.13" x 15.35"
Height	4.26”
Mounting	Clip-in
Color selection	Selectable CCT

Color temperature	27,30,35,41,50K
Lumens per head	1225/1700
Luminous flux	4900/6800
CRI	90>
Beam angle	40° (Default)
Tilt angle	30°
Rotation	360°
Power	80/50W
Voltage	120-277V
Output current	1850/1260mA
Plenum rating	FT6
Dimming type	Triac Or 0-10V Dimming
Dimming range	100 - 5%
Location rating	Wet
IC rated	Only at 50W
Listed certifications	ETL, Title24 Listed

Request pricing & availability

Request a product quote at truled.com

Include any configuration reference, quantities, required lengths and project location.

A configuration reference identifies a published specification row. A row may list multiple options; it is not confirmation that every option is included. This sheet is not an installation instruction or an approved project submittal.