SIGN & BACKLIGHT STRIPS

White S-Bend 24V 60LED/M 6mm LED strip

TRU-SB24V6MM60LEDM

White S-Bend 24V 60LED/M 6mm LED strip. Review the dimensions and electrical ratings for your installation.

Use this catalog sheet to discuss your project. Final dimensions, ratings, certifications and available configurations must be confirmed for the selected product.



Product specifications

Truled part number	TRU-SB24V6MM60LEDM
Category	LED strips
Product type	Sign & backlight strips
Dimension	L5000*W6*H1mm [L197*W0.24*H0.04in]
Increment	100mm [3.94in]
LED Type	SMD 2835
LED Qty	60LED/M [18LED/ft.]
Voltage	24VDC
Power	7.2W/M [2.2W/ft.]
CCT / Wavelength	2700K&3000K& 3500K&4000K& 5000K&6500K, AM: amber 1600K R:625~630nm, G:520~525nm, B:460~47Onm, Y: yellow 585~595nm, Pl: pink
Brightness @CRI80&4000K	720lm/M [220lm/ft.]
Light Efficiency @CRI80&4000K	100lm/W
Brightness @CRI90&4000K	610lm/M [186lm/ft.]
Light Efficiency @CRI90&4000K	85lm/W

Beam Angle	120°
IP Rating	IP20 [Dry]

Request pricing & availability

Request a product quote at truled.com

Include any configuration reference, quantities, required lengths and project location.

A configuration reference identifies a published specification row. A row may list multiple options; it is not confirmation that every option is included. This sheet is not an installation instruction or an approved project submittal.