SIGN & BACKLIGHT STRIPS

Spliceable Grid White 24V 20LED/M 16mm LED strip

TRU-SBA24V16MM20LEDM

Spliceable Grid White 24V 20LED/M 16mm LED strip. Review the dimensions and electrical ratings for your installation.

Use this catalog sheet to discuss your project. Final dimensions, ratings, certifications and available configurations must be confirmed for the selected product.



Product specifications

Truled part number	TRU-SBA24V16MM20LEDM
Category	LED strips
Product type	Sign & backlight strips
Dimension	L9600*W16*H6.5mm [L378*W0.63*H0.26in]
Increment	100mm [3.94in]
LED Type	SMD 2835
LED Qty	20LED/M [6LED/ft.]
Voltage	24VDC
Power	9.6W/M [2.93W/ft.]
CCT / Wavelength	2700K 3000K 3500K 4000K 5000K 6500K
Brightness @CRI80&4000K	1132lm/M [345lm/ft.]
Light Efficiency @CRI80&4000K	118lm/M
Brightness @CRI90&4000K	960lm/M [293lm/ft.]
Light Efficiency @CRI90&4000K	100lm/M

Beam Angle	180° With lens
IP Rating	IP20 [Dry]

Request pricing & availability

Request a product quote at truled.com

Include any configuration reference, quantities, required lengths and project location.

A configuration reference identifies a published specification row. A row may list multiple options; it is not confirmation that every option is included. This sheet is not an installation instruction or an approved project submittal.