
SIGN & BACKLIGHT STRIPS

Light Sheet High-Eff. 24V 610*305mm LED strip

TRU-SBB24V305MM

Light Sheet High-Eff. 24V 610*305mm LED strip. Review the dimensions and electrical ratings for your installation.

Use this catalog sheet to discuss your project. Final dimensions, ratings, certifications and available configurations must be confirmed for the selected product.



Product specifications

Truled part number	TRU-SBB24V305MM
Category	LED strips
Product type	Sign & backlight strips
Dimension	L610*W305*H1mm [L24*W12*H0.04in.]
Increment	L101.6*W101.6mm [L4*W4in.]
LED Type	SMD 2835
LED Qty	288LED/Sheet
Voltage	24VDC
Power	20W
CCT / Wavelength	2700~6500K (CCT~tunable)
Brightness @CRI80	1470lm/sheet (2700K) 1590lm/sheet (6500K) 82lm/unit (2700K) 88lm/unit (6500K) 7900lm/m2 (2700K) 8550lm/m2 (6500K) [730lm/ft2.] (2700K) [790lm/ft2.] (6500K)
Light Efficiency @CRI80	147lm/W (2700K) 159lm/W (6500K)
Brightness @CRI90	1250lm/sheet (2700K) 1350lm/sheet (6500K) 69lm/unit (2700K) 75lm/unit (6500K) 6720lm/m2 (2700K) 7260lm/m2 (6500K) [620lm/ft2.] (2700K) [670lm/ft2.] (6500K)
Light Efficiency @CRI90	126lm/W (2700K) 136lm/W (6500K)

Beam Angle	120°
IP Rating	IP20/ IP54 Thin [Dry/Damp]

Request pricing & availability

Request a product quote at truled.com

Include any configuration reference, quantities, required lengths and project location.

A configuration reference identifies a published specification row. A row may list multiple options; it is not confirmation that every option is included. This sheet is not an installation instruction or an approved project submittal.