COB STRIPS

White High-Eff. Prem. 130lm/W 24V 320LED/M 8mm LED strip

TRU-SCO24V8MM320LEDM

White High-Eff. Prem. 130lm/W 24V 320LED/M 8mm LED strip. Review the dimensions and electrical ratings for your installation.

Use this catalog sheet to discuss your project. Final dimensions, ratings, certifications and available configurations must be confirmed for the selected product.



Product specifications

Truled part number	TRU-SCO24V8MM320LEDM
Category	LED strips
Product type	COB strips

Configuration reference

TRU-SCO24V8MM320LEDM-A

Dimension	L5000*W8*H2.3mm [L197*W0.31*H0.09in.]
Increment	25mm [0.98in.]
LED Type	SMD 2216
LED Qty	320LEDs/M [98LEDs/ft.]
Voltage	24VDC
Power	16.8W/M [5.12W/ft.]
CCT / Wavelength	2700K 3000K 4000K 5000K 6500K
Brightness	1966lm/M[599lm/ft.] (2700K)
Light Efficiency	117lm/W (2700K)
Brightness	2100lm/M[640lm/ft.] (3000K)
Light Efficiency	125lm/W (3000K)
Brightness	2184lm/M[666lm/ft.] (4000K)
Light Efficiency	130lm/W (4000K)
Beam Angle	150°
IP Rating	IP20 [Dry]

Configuration reference

TRU-SCO24V8MM320LEDM-B

Dimension	L5000*W8*H2.3mm [L197*W0.31*H0.09in.]
Increment	25mm [0.98in.]
LED Type	SMD 2216
LED Qty	320LEDs/M [98LEDs/ft.]
Voltage	24VDC
Power	16.8W/M [5.12W/ft.]
CCT / Wavelength	2700K 3000K 4000K 5000K 6500K
Brightness	2184lm/M[666lm/ft.] (5000K)
Light Efficiency	130lm/W (5000K)
Brightness	2184lm/M[666lm/ft.] (6500K)
Light Efficiency	130lm/W (6500K)
Brightness	Not specified
Light Efficiency	Not specified
Beam Angle	150°
IP Rating	IP20 [Dry]

Request pricing & availability

Request a product quote at truled.com

Include any configuration reference, quantities, required lengths and project location.

A configuration reference identifies a published specification row. A row may list multiple options; it is not confirmation that every option is included. This sheet is not an installation instruction or an approved project submittal.