COB STRIPS

White Free-Cutting 24V 240LEDs/M 10mm LED strip

TRU-SCOD24V

White Free-Cutting 24V 240LEDs/M 10mm LED strip. Review the dimensions and electrical ratings for your installation.

Use this catalog sheet to discuss your project. Final dimensions, ratings, certifications and available configurations must be confirmed for the selected product.



Product specifications

Truled part number	TRU-SCOD24V
Category	LED strips
Product type	COB strips

Configuration reference

TRU-SCOD24V-A

Dimension	L5000*W10*H3.8mm [L197*W0.39*H0.15in.]
Increment	Free cutting to be any length
LED Type	SMD 2835
LED Qty	240LEDs/M [73LEDs/ft.]
Voltage	24VDC
Power	19.2W/M [5.85W/ft.]
CCT / Wavelength	2700K 3000K 4000K 5000K 6500K
Brightness	2025lm/M[617lm/ft.] (2700K)
Light Efficiency	106lm/W (2700K)
Brightness	2215lm/M[675lm/ft.] (3000K)
Light Efficiency	116lm/W (3000K)
Brightness	2320lm/M[707lm/ft.] (4000K)
Light Efficiency	121lm/W (4000K)
Beam Angle	150°
IP Rating	IP20 [Dry]

Configuration reference

TRU-SCOD24V-B

Dimension	L5000*W10*H3.8mm [L197*W0.39*H0.15in.]
Increment	Free cutting to be any length
LED Type	SMD 2835
LED Qty	240LEDs/M [73LEDs/ft.]
Voltage	24VDC
Power	19.2W/M [5.85W/ft.]
CCT / Wavelength	2700K 3000K 4000K 5000K 6500K
Brightness	2320lm/M[707lm/ft.] (5000K)
Light Efficiency	121lm/W (5000K)
Brightness	2320lm/M[707lm/ft.] (6500K)
Light Efficiency	121lm/W (6500K)
Brightness	Not specified
Light Efficiency	Not specified
Beam Angle	150°
IP Rating	IP20 [Dry]

Configuration reference

TRU-SCOD24V-C

Dimension	L5000*W10*H3.8mm [L197*W0.39*H0.15in.]
Increment	Free cutting to be any length
LED Type	SMD 2835
LED Qty	240LEDs/M [73LEDs/ft.]
Voltage	24VDC
Power	19.2W/M [5.85W/ft.]
CCT / Wavelength	2700K 3000K 4000K 5000K 6500K
Brightness	2295lm/M[700lm/ft.] (2700K)
Light Efficiency	120lm/W (2700K)
Brightness	2510lm/M[765lm/ft.] (3000K)
Light Efficiency	131lm/W (3000K)
Brightness	2630lm/M[802lm/ft.] (4000K)
Light Efficiency	137lm/W (4000K)
Beam Angle	150°
IP Rating	IP20 [Dry]

Configuration reference

TRU-SCOD24V-D

Dimension	L5000*W10*H3.8mm [L197*W0.39*H0.15in.]
Increment	Free cutting to be any length
LED Type	SMD 2835
LED Qty	240LEDs/M [73LEDs/ft.]
Voltage	24VDC
Power	19.2W/M [5.85W/ft.]
CCT / Wavelength	2700K 3000K 4000K 5000K 6500K
Brightness	2630lm/M[802lm/ft.] (5000K)
Light Efficiency	137lm/W (5000K)
Brightness	2630lm/M[802lm/ft.] (6500K)
Light Efficiency	137lm/W (6500K)
Brightness	Not specified
Light Efficiency	Not specified
Beam Angle	150°
IP Rating	IP20 [Dry]

Request pricing & availability

Request a product quote at truled.com

Include any configuration reference, quantities, required lengths and project location.

A configuration reference identifies a published specification row. A row may list multiple options; it is not confirmation that every option is included. This sheet is not an installation instruction or an approved project submittal.