COB STRIPS

White Free-Cutting 24V 320LED/M 8mm LED strip

TRU-SCOE24V8MM

White Free-Cutting 24V 320LED/M 8mm LED strip. Review the dimensions and electrical ratings for your installation.



Use this catalog sheet to discuss your project. Final dimensions, ratings, certifications and available configurations must be confirmed for the selected product.

Product specifications

Truled part number	TRU-SCOE24V8MM
Category	LED strips
Product type	COB strips

Configuration reference

TRU-SCOE24V8MM-A

Dimension	L5000*W8*H2.5mm [L197*W0.39*H0.1in.]
Increment	Free-cutting to be any length
LED Type	SMD 2216
LED Qty	320chips/M [98chips/ft.]
Voltage	24VDC
Power	15W/M [4.6W/ft.]
CCT / Wavelength	2700K 3000K 4000K 5000K 6500K
Brightness	1440lm/M[439lm/ft.] (2700K)
Light Efficiency	96lm/W (2700K)
Brightness	1575lm/M[480lm/ft.] (3000K)
Light Efficiency	105lm/W (3000K)
Brightness	1650lm/M[503lm/ft.] (4000K)
Light Efficiency	110lm/W (4000K)
Beam Angle	150°
IP Rating	IP20/ IP65/ IP67 Plus [Dry/Wet]

Configuration reference

TRU-SCOE24V8MM-B

Dimension	L5000*W8*H2.5mm [L197*W0.39*H0.1in.]
Increment	Free-cutting to be any length
LED Type	SMD 2216
LED Qty	320chips/M [98chips/ft.]
Voltage	24VDC
Power	15W/M [4.6W/ft.]
CCT / Wavelength	2700K 3000K 4000K 5000K 6500K
Brightness	1650lm/M[503lm/ft.] (5000K)
Light Efficiency	110lm/W (5000K)
Brightness	1650lm/M[503lm/ft.] (6500K)
Light Efficiency	110lm/W (6500K)
Brightness	Not specified
Light Efficiency	Not specified
Beam Angle	150°
IP Rating	IP20/ IP65/ IP67 Plus [Dry/Wet]

Request pricing & availability

Request a product quote at truled.com

Include any configuration reference, quantities, required lengths and project location.

A configuration reference identifies a published specification row. A row may list multiple options; it is not confirmation that every option is included. This sheet is not an installation instruction or an approved project submittal.