
TUNABLE WHITE STRIPS

Light Sheet High-Eff. CCT 24V 480*240mm LED strip

TRU-SCTA24V240MM

Light Sheet High-Eff. CCT 24V 480*240mm LED strip. Review the dimensions and electrical ratings for your installation.

Use this catalog sheet to discuss your project. Final dimensions, ratings, certifications and available configurations must be confirmed for the selected product.



Product specifications

Truled part number	TRU-SCTA24V240MM
Category	LED strips
Product type	Tunable white strips

Configuration reference

TRU-SCTA24V240MM-A

Dimension	L480*W240*H2mm [L19*W9.5*H0.08in]
Increment	L160*W80mm [L6.3*W3.2in.]
LED Type	SMD 2835
LED Qty	504LED/Sheet
Voltage	24VDC
Power	20W
CCT / Wavelength	2700-6500K (CCT-Tunable)
Brightness @CRI80&4000K	2600lm/sheet, 8.7lm/unit piece 22580lm/m2 [2080lm/ft2.]
Light Efficiency @CRI80&4000K	130lm/W
Brightness @CRI90&4000K	2210lm/sheet, 7.6lm/unit piece 19200lm/m2 [1760lm/ft2.]
Beam Angle	120°
IP Rating	IP20/ IP54 Thin [Dry/Damp]

Configuration reference

TRU-SCTA24V240MM-B

Dimension	L480*W240*H2mm [L19*W9.5*H0.08in]
Increment	L160*W80mm [L6.3*W3.2in.]
LED Type	SMD 2835
LED Qty	504LED/Sheet
Voltage	24VDC
Power	40W
CCT / Wavelength	2700-6500K (CCT-Tunable)
Brightness @CRI80&4000K	5080lm/sheet, 18.3lm/unit piece 46090lm/m2 [4240lm/ft2.]
Light Efficiency @CRI80&4000K	127lm/W
Brightness @CRI90&4000K	4520lm/sheet, 15.5lm/unit piece 39160lm/m2 [3620lm/ft2.]
Beam Angle	120°
IP Rating	IP20/ IP54 Thin [Dry/Damp]

Configuration reference

TRU-SCTA24V240MM-C

Dimension	L480*W240*H2mm [L19*W9.5*H0.08in]
Increment	L160*W80mm [L6.3*W3.2in.]
LED Type	SMD 2835
LED Qty	504LED/Sheet
Voltage	24VDC
Power	60W
CCT / Wavelength	2700-6500K (CCT-Tunable)
Brightness @CRI80&4000K	7380lm/sheet, 25.5lm/unit piece 64910lm/m2 [5900lm/ft2.]
Light Efficiency @CRI80&4000K	123lm/W
Brightness @CRI90&4000K	6290lm/sheet, 21.9lm/unit piece 55180lm/m2 [5030lm/ft2.]
Beam Angle	120°
IP Rating	IP20/ IP54 Thin [Dry/Damp]

Configuration reference

TRU-SCTA24V240MM-D

Dimension	L480*W240*H2mm [L19*W9.5*H0.08in]
Increment	L160*W80mm [L6.3*W3.2in.]
LED Type	SMD 2835
LED Qty	504LED/Sheet
Voltage	24VDC
Power	90W
CCT / Wavelength	2700-6500K (CCT-Tunable)
Brightness @CRI80&4000K	10890lm/sheet, 38.4lm/unit piece 94910lm/m2 [8710lm/ft2.]
Light Efficiency @CRI80&4000K	121lm/W
Brightness @CRI90&4000K	9160lm/sheet, 33lm/unit piece 80690lm/m2 [7400lm/ft2.]
Beam Angle	120°
IP Rating	IP20/ IP54 Thin [Dry/Damp]

Request pricing & availability

Request a product quote at truled.com

Include any configuration reference, quantities, required lengths and project location.

A configuration reference identifies a published specification row. A row may list multiple options; it is not confirmation that every option is included. This sheet is not an installation instruction or an approved project submittal.