TUNABLE WHITE STRIPS

Dim-to-Warm PWM Pro 24V 252LED/M 12mm LED strip

TRU-SCTB24V

Dim-to-Warm PWM Pro 24V 252LED/M 12mm LED strip. Review the dimensions and electrical ratings for your installation.

Use this catalog sheet to discuss your project. Final dimensions, ratings, certifications and available configurations must be confirmed for the selected product.



Product specifications

Truled part number	TRU-SCTB24V
Category	LED strips
Product type	Tunable white strips

Configuration reference

TRU-SCTB24V-A

Dimension	L5000*W12*H1mm [L197*W0.47*H0.04in]
Increment	55.6mm [2.19in.]
LED Type	SMD2216
LED Qty	252LED/M [76LED/ft.]
Voltage	24VDC
Power	15W/M [4.57W/ft.]
CCT / Wavelength	1800~3000K (Dim-to-warm)
Brightness @CRI90&3000K	1100lm/M [330lm/ft.]
Light Efficiency @CRI90&3000K	73lm/W
Beam Angle	120°
IP Rating	IP20/ IP65 [Dry/Wet]

Configuration reference

TRU-SCTB24V-B

Dimension	L5000*W12*H1mm [L197*W0.47*H0.04in]
Increment	55.6mm [2.19in.]
LED Type	SMD2216
LED Qty	252LED/M [76LED/ft.]
Voltage	24VDC
Power	9.3W/M [2.93W/ft.]
CCT / Wavelength	1800~3000K (Dim-to-warm)
Brightness @CRI90&3000K	730lm/M [220lm/ft.]
Light Efficiency @CRI90&3000K	76lm/W
Beam Angle	120°
IP Rating	IP20/ IP65 [Dry/Wet]

Request pricing & availability

Request a product quote at truled.com

Include any configuration reference, quantities, required lengths and project location.

A configuration reference identifies a published specification row. A row may list multiple options; it is not confirmation that every option is included. This sheet is not an installation instruction or an approved project submittal.