LONG-RUN STRIPS

White 20M Short-Cutting 24V 120LED/M 10mm LED strip

TRU-SLR24V120LEDM

White 20M Short-Cutting 24V 120LED/M 10mm LED strip. Review the dimensions and electrical ratings for your installation.

Use this catalog sheet to discuss your project. Final dimensions, ratings, certifications and available configurations must be confirmed for the selected product.



Product specifications

Truled part number	TRU-SLR24V120LEDM
Category	LED strips
Product type	Long-run strips

Configuration reference

TRU-SLR24V120LEDM-A

Dimension	L10000*W10*H1mm [L394*W0.39*H0.04in.]
Increment	8.33mm [0.33in.]
LED Type	SMD2835
LED Qty	120LED/M [36LED/ft.]
Voltage	24VDC
Power	10W/M [3.05W/ft.]
CCT / Wavelength	2700K 3000K 3500K 4000K 5000K 6500K
Brightness @CRI80&4000K	240lm/M [73lm/ft.]
Light Efficiency @CRI80&4000K	110lm/W
Brightness @CRI90&4000K	940lm/M [285lm/ft.]
Light Efficiency @CRI90&4000K	94lm/W
Beam Angle	120°
IP Rating	IP20/ IP54/ IP54 Plus/ IP65/ IP67/ IP67 Plus Thin/ IP67 Plus/ IP68 [Dry/Damp/Wet]

Configuration reference

TRU-SLR24V120LEDM-B

Dimension	L20000*W10*H1mm [L788*W0.39*H0.04in.]
Increment	8.33mm [0.33in.]
LED Type	SMD2835
LED Qty	120LED/M [36LED/ft.]
Voltage	24VDC
Power	4W/M [1.22W/ft.]
CCT / Wavelength	2700K 3000K 3500K 4000K 5000K 6500K
Brightness @CRI80&4000K	440lm/M [130lm/ft.]
Light Efficiency @CRI80&4000K	110lm/W
Brightness @CRI90&4000K	380lm/M [115lm/ft.]
Light Efficiency @CRI90&4000K	94lm/W
Beam Angle	120°
IP Rating	IP20/ IP54/ IP54 Plus/ IP65/ IP67/ IP67 Plus Thin/ IP67 Plus/ IP68 [Dry/Damp/Wet]

Request pricing & availability

Request a product quote at truled.com

Include any configuration reference, quantities, required lengths and project location.

A configuration reference identifies a published specification row. A row may list multiple options; it is not confirmation that every option is included. This sheet is not an installation instruction or an approved project submittal.