LONG-RUN STRIPS

White 25M High-Efficacy 24V 126LED/M 10mm LED strip

TRU-SLR24V126LEDM

White 25M High-Efficacy 24V 126LED/M 10mm LED strip. Review the dimensions and electrical ratings for your installation.

Use this catalog sheet to discuss your project. Final dimensions, ratings, certifications and available configurations must be confirmed for the selected product.



Product specifications

Truled part number	TRU-SLR24V126LEDM
Category	LED strips
Product type	Long-run strips

Configuration reference

TRU-SLR24V126LEDM-A

Dimension	L10000*W10*H1mm [L394*W0.39*H0.04in.]
Increment	55.6mm [2.2in.]
LED Type	SMD2835
LED Qty	126LED/M [38LED/ft.]
Voltage	24VDC
Power	15W/M [4.6W/ft.]
CCT / Wavelength	2700K 3000K 3500K 4000K 5000K 6500K
Brightness @CRI80&4000K	1810lm/M [550lm/ft.]
Light Efficiency @CRI80&4000K	121lm/W
Brightness @CRI90&4000K	1540lm/M [470lm/ft.]
Light Efficiency @CRI90&4000K	103lm/W
Beam Angle	120°
IP Rating	IP20/ IP54 Plus/ IP67 Plus Thin/ IP67 Plus [Dry/Damp]

Configuration reference

TRU-SLR24V126LEDM-B

Dimension	L15000*W10*H1mm [L591*W0.39*H0.04in.]
Increment	55.6mm [2.2in.]
LED Type	SMD2835
LED Qty	126LED/M [38LED/ft.]
Voltage	24VDC
Power	8W/M [2.4W/ft.]
CCT / Wavelength	2700K 3000K 3500K 4000K 5000K 6500K
Brightness @CRI80&4000K	1020lm/M [310lm/ft.]
Light Efficiency @CRI80&4000K	128lm/W
Brightness @CRI90&4000K	870lm/M [270lm/ft.]
Light Efficiency @CRI90&4000K	109lm/W
Beam Angle	120°
IP Rating	IP20/ IP54 Plus/ IP67 Plus Thin/ IP67 Plus [Dry/Damp]

Configuration reference

TRU-SLR24V126LEDM-C

Dimension	L25000*W10*H1mm [L984*W0.39*H0.04in.]
Increment	55.6mm [2.2in.]
LED Type	SMD2835
LED Qty	126LED/M [38LED/ft.]
Voltage	24VDC
Power	4.5W/M [1.4W/ft.]
CCT / Wavelength	2700K 3000K 3500K 4000K 5000K 6500K
Brightness @CRI80&4000K	550lm/M [170lm/ft.]
Light Efficiency @CRI80&4000K	122lm/W
Brightness @CRI90&4000K	470lm/M [140lm/ft.]
Light Efficiency @CRI90&4000K	104lm/W
Beam Angle	120°
IP Rating	IP20/ IP54 Plus/ IP67 Plus Thin/ IP67 Plus [Dry/Damp]

Request pricing & availability

Request a product quote at truled.com

Include any configuration reference, quantities, required lengths and project location.

A configuration reference identifies a published specification row. A row may list multiple options; it is not confirmation that every option is included. This sheet is not an installation instruction or an approved project submittal.