DIGITAL & PIXEL STRIPS

SPI RGBW 15M 48V 60LED/M 12mm LED strip

TRU-SPX48V60LEDM

SPI RGBW 15M 48V 60LED/M 12mm LED strip. Review the dimensions and electrical ratings for your installation.

Use this catalog sheet to discuss your project. Final dimensions, ratings, certifications and available configurations must be confirmed for the selected product.



Product specifications

Truled part number	TRU-SPX48V60LEDM
Category	LED strips
Product type	Digital & pixel strips
Dimension	15000*12*2.3mm [591*0.47*0.09in.]
Increment	250mm [9.84in.]
LED Type	SMD5050 4in1
LED Qty	60LED/M [18LED/ft.]
Voltage	48VDC
Power	14.4W/M [4.39W/ft.] (4.8W/color)
CCT / Wavelength	R: 620~630nm, G: 520~530nm, B: 450~460nm W: 2700K~6500K
Brightness @Mix	778lm/M [237lm/ft.]
Brightness @Red	96lm/M [29lm/ft.]
Brightness @Green	312lm/M [95lm/ft.]
Brightness @Blue	67lm/M [20lm/ft.]

Brightness @White	336lm/M [102lm/ft.]
Beam Angle	120°
IP Rating	IP20/ IP54 Plus/ IP67 Plus [Dry/Damp/Wet]

Request pricing & availability

Request a product quote at truled.com

Include any configuration reference, quantities, required lengths and project location.

A configuration reference identifies a published specification row. A row may list multiple options; it is not confirmation that every option is included. This sheet is not an installation instruction or an approved project submittal.