DIGITAL & PIXEL STRIPS

SPI RGB 1-LED Per Pixel 5V 60LED/M 8mm LED strip

TRU-SPX5V8MM60LEDM

SPI RGB 1-LED Per Pixel 5V 60LED/M 8mm LED strip. Review the dimensions and electrical ratings for your installation.

Use this catalog sheet to discuss your project. Final dimensions, ratings, certifications and available configurations must be confirmed for the selected product.



Product specifications

Truled part number	TRU-SPX5V8MM60LEDM
Category	LED strips
Product type	Digital & pixel strips
Dimension	L3000*W8*H2.6mm [L118*W0.32*H0.1in.]
Increment	16.7mm [0.66in.]
LED Type	SMD 4020 (Built-in SPI IC)
LED Qty	60LED/M [18LED/ft.]
Voltage	5VDC
Power	10.5W/M [3.2W/ft.]
CCT / Wavelength	R: 620~625nm G: 520~525nm B: 465~470nm
Lumen Flux @Mix	280lm/M [85lm/ft.]
Lumen Flux @Red	60lm/M [18lm/ft.]
Lumen Flux @Green	175lm/M [53lm/ft.]
Lumen Flux @Blue	45lm/M [14lm/ft.]

Beam Angle	80°
IP Rating	IP20/IP65 [Dry/Wet]

Request pricing & availability

Request a product quote at truled.com

Include any configuration reference, quantities, required lengths and project location.

A configuration reference identifies a published specification row. A row may list multiple options; it is not confirmation that every option is included. This sheet is not an installation instruction or an approved project submittal.