DIGITAL & PIXEL STRIPS

# Light Sheet SPI RGBW 24V 610*305mm LED strip

**TRU-SPXA24V305MM**

Light Sheet SPI RGBW 24V 610*305mm LED strip. Review the dimensions and electrical ratings for your installation.

Use this catalog sheet to discuss your project. Final dimensions, ratings, certifications and available configurations must be confirmed for the selected product.



## Product specifications

| | |
|---|---|
| Truled part number | TRU-SPXA24V305MM |
| Category | LED strips |
| Product type | Digital & pixel strips |
| Dimension | L610*W305*H2mm [L24*W12*H0.08in.] |
| Increment | L101.6*W101.6mm [L4*W4in.] |
| LED Type | SMD 5050 |
| LED Qty | 216LED/Sheet |
| Voltage | 24VDC |
| Power | 32W |
| CCT / Wavelength | R: 625~630nm, G: 520~525nm, B: 460~470nm, W: 2700K&3000K& 3500K&4000K& 5000K&6500K |
| Brightness @CRI80&4000K | 850lm/sheet, 48lm/unit 4570lm/m2 [430lm/ft2.] |
| Brightness @Red | 280lm/sheet, 15lm/unit 1510lm/m2 [140lm/ft2.] |
| Brightness @Green | 800lm/sheet, 36lm/unit 3520lm/m2 [330lm/ft2.] |
| Brightness @Blue | 160lm/sheet, 8.5lm/unit 860lm/m2 [80lm/ft2.] |

| | |
|---|---|
| Beam Angle | 120° |
| IP Rating | IP20/ IP54 Thin [Dry/Damp] |

## Request pricing & availability

Request a product quote at truled.com

Include any configuration reference, quantities, required lengths and project location.

A configuration reference identifies a published specification row. A row may list multiple options; it is not confirmation that every option is included. This sheet is not an installation instruction or an approved project submittal.