DIGITAL & PIXEL STRIPS

SPI RGBW 24V 120LED/M 12mm LED strip

TRU-SPXI24V

SPI RGBW 24V 120LED/M 12mm LED strip. Review the dimensions and electrical ratings for your installation.

Use this catalog sheet to discuss your project. Final dimensions, ratings, certifications and available configurations must be confirmed for the selected product.



Product specifications

Truled part number	TRU-SPXI24V
Category	LED strips
Product type	Digital & pixel strips
Dimension	L5000*W12*H2mm [L197*W0.47*H0.08in.]
Increment	50mm [1.97in.]
LED Type	SMD4040 RGBW 4in1
LED Qty	120LEDs/M [36LEDs/ft.]
Voltage	24VDC
Power	28W/M [8.53W/ft.]
CCT / Wavelength	R: 620~635nm, G: 520~530nm, B: 460~470nm W: 2700/3000/ 3500/4000/ 5000/6500K
Brightness @Mix	1215lm/M [370lm/ft.]
Brightness @Red	183lm/M [56lm/ft.]
Brightness @Green	520lm/M [158lm/ft.]
Brightness @Blue	110lm/M [34lm/ft.]

Brightness @4000K&CRI90	540lm/M [165lm/ft.]
Beam Angle	120°
IP Rating	IP20 [Dry]

Request pricing & availability

Request a product quote at truled.com

Include any configuration reference, quantities, required lengths and project location.

A configuration reference identifies a published specification row. A row may list multiple options; it is not confirmation that every option is included. This sheet is not an installation instruction or an approved project submittal.