RGB STRIPS

RGB 25M 48V 78LED/M 12mm LED strip

TRU-SRGB48V78LEDM

RGB 25M 48V 78LED/M 12mm LED strip. Review the dimensions and electrical ratings for your installation.

Use this catalog sheet to discuss your project. Final dimensions, ratings, certifications and available configurations must be confirmed for the selected product.



Product specifications

Truled part number	TRU-SRGB48V78LEDM
Category	LED strips
Product type	RGB strips

Configuration reference

TRU-SRGB48V78LEDM-A

Dimension	L15000*W12*H2mm [L591*W0.48*H0.08in.]
Increment	166.7mm [6.56in.]
LED Type	SMD5050 RGB
LED Qty	78LED/M [23LED/ft.]
Voltage	48VDC
Power	15.6W/M [4.76W/ft.]
CCT / Wavelength	R:625-630nm G:520~525nm B:460~470nm
Brightness @Mix&CRI80	615lm/M [188lm/ft.]
Brightness @Red	180lm/M [55lm/ft.]
Brightness @Green	350lm/M [107lm/ft.]
Brightness @Blue	85lm/M [26lm/ft.]
Beam Angle	120°
IP Rating	IP20/ IP67 Plus [Dry/Wet]

Configuration reference

TRU-SRGB48V78LEDM-B

Dimension	L25000*W12*H2mm [L984*W0.48*H0.08in.]
Increment	166.7mm [6.56in.]
LED Type	SMD5050 RGB
LED Qty	78LED/M [23LED/ft.]
Voltage	48VDC
Power	10W/M [3.05W/ft.]
CCT / Wavelength	R:625-630nm G:520~525nm B:460~470nm
Brightness @Mix&CRI80	400lm/M [122lm/ft.]
Brightness @Red	120lm/M [37lm/ft.]
Brightness @Green	225lm/M [69lm/ft.]
Brightness @Blue	55lm/M [17lm/ft.]
Beam Angle	120°
IP Rating	IP20/ IP67 Plus [Dry/Wet]

Request pricing & availability

Request a product quote at truled.com

Include any configuration reference, quantities, required lengths and project location.

A configuration reference identifies a published specification row. A row may list multiple options; it is not confirmation that every option is included. This sheet is not an installation instruction or an approved project submittal.