
SPECIALTY APPLICATION STRIPS

Ta=125°C RGBW 24V 840LED/M 12mm LED strip

TRU-SSP24V840LEDM

Ta=125°C RGBW 24V 840LED/M 12mm LED strip. Review the dimensions and electrical ratings for your installation.

Use this catalog sheet to discuss your project. Final dimensions, ratings, certifications and available configurations must be confirmed for the selected product.



Product specifications

Truled part number	TRU-SSP24V840LEDM
Category	LED strips
Product type	Specialty application strips
Dimension	L5000*W14*H6mm [L197*W0.55*H0.24in.]]
Increment	33.33mm [1.31in.]
LED Type	COB (Chip On Board)
LED Qty	840LED/M [256LED/ft.]
Voltage	24VDC
Power	9.6W/M [2.93W/ft.]
CCT / Wavelength	R: 620-630nm G: 525-535nm B: 450-460nm W: 2700K/3000K/ 3500K/4000K/ 5000K/6500K
Brightness @RGBW	540lm/M [165lm/ft.]
Brightness @Red	80lm/M [24lm/ft.]
Brightness @Green	240lm/M [73lm/ft.]
Brightness @Blue	36lm/M [11lm/ft.]

Brightness @4000K	184lm/M [56lm/ft.]
Beam Angle	150°
IP Rating	IP67 Plus [Wet]

Request pricing & availability

Request a product quote at truled.com

Include any configuration reference, quantities, required lengths and project location.

A configuration reference identifies a published specification row. A row may list multiple options; it is not confirmation that every option is included. This sheet is not an installation instruction or an approved project submittal.