
SPECIALTY APPLICATION STRIPS

Ta=60°C 48V 130LED/M LED strip

TRU-SSP48V

Ta=60°C 48V 130LED/M LED strip. Review the dimensions and electrical ratings for your installation.

Use this catalog sheet to discuss your project. Final dimensions, ratings, certifications and available configurations must be confirmed for the selected product.



Product specifications

Truled part number	TRU-SSP48V
Category	LED strips
Product type	Specialty application strips
Dimension	L25000*W12*H6mm [L[984*W0.47*H0.23in.]
Max. Length (La)	25M [82ft.]
Increment	100mm [3.94in.]
LED Type	SMD 2835
LED Qty	130LED/M [39LED/ft.]
Voltage	DC48V
Power	9.6W/M [2.93W/ft.]
CCT/Wavelength	2700K 3000K 4000K 5000K 6500K (3 step in 1 bin)
Brightness @3000K&CRI80	980lm/M [299lm/ft.]
Light Efficiency @3000K&CRI80	102lm/W
Brightness @4000K&CRI90	1050lm/M [320lm/ft.]

Light Efficiency @4000K&CRI90	109lm/W
Beam Angle	120°
IP&IK Rating	IP67 [Dry/Damp]

Request pricing & availability

Request a product quote at truled.com

Include any configuration reference, quantities, required lengths and project location.

A configuration reference identifies a published specification row. A row may list multiple options; it is not confirmation that every option is included. This sheet is not an installation instruction or an approved project submittal.