
SPECIALTY APPLICATION STRIPS

Ta=100°C 24V 120LED/M 16.5mm LED strip

TRU-SSPA24V

Ta=100°C 24V 120LED/M 16.5mm LED strip. Review the dimensions and electrical ratings for your installation.

Use this catalog sheet to discuss your project. Final dimensions, ratings, certifications and available configurations must be confirmed for the selected product.



Product specifications

Truled part number	TRU-SSPA24V
Category	LED strips
Product type	Specialty application strips
Style	Top-Bend (Dual Colors Silicone Extrusion)
Dimension	L10000*W16.5*H7mm [L394*W0.65*H0.28in.]]
Increment	50mm [1.97in.]
LED Type	SMD2835
LED Qty	120LED/M [36LED/ft.]
Voltage	24VDC
Power	9.6W/M [2.93W/ft.]
CCT / Wavelength	2700K 3000K 3500K 4000K 5000K 6500K
Brightness @3000K&CRI80	1000lm/M [305lm/ft.]
Light Efficiency @3000K&CRI80	104lm/W
Brightness @3000K&CRI90	850lm/M [260lm/ft.]

Light Efficiency @3000K&CRI90	89lm/W
Beam Angle	120°
IP Rating	IP67 Plus [Wet]

Request pricing & availability

Request a product quote at truled.com

Include any configuration reference, quantities, required lengths and project location.

A configuration reference identifies a published specification row. A row may list multiple options; it is not confirmation that every option is included. This sheet is not an installation instruction or an approved project submittal.