SPECIALTY APPLICATION STRIPS

Ta=125°C CCT 24V 608LED/M 12mm LED strip

TRU-SSPF24V

Ta=125°C CCT 24V 608LED/M 12mm LED strip. Review the dimensions and electrical ratings for your installation.

Use this catalog sheet to discuss your project. Final dimensions, ratings, certifications and available configurations must be confirmed for the selected product.



Product specifications

Truled part number	TRU-SSPF24V
Category	LED strips
Product type	Specialty application strips
Dimension	L5000*W12*H5.5mm [L197*W0.47*H0.22in.]]
Increment	26.3mm [1.04in.]
LED Type	COB (Chip On Board)
LED Qty	608LED/M [146LED/ft.]
Voltage	24VDC
Power	8W/M [2.44W/ft.]
CCT / Wavelength	2700K~6500K CCT-Tunable
Brightness @CRI90&2700K	695lm/M [212lm/ft.]
Light Efficiency @CRI90&2700K	87lm/W
Brightness @CRI90&6500K	845lm/M [258lm/ft.]
Light Efficiency @CRI90&6500K	105lm/W

Brightness @CRI90&Mix	955lm/M [291lm/ft.]
Light Efficiency @CRI90&Mix	96lm/W
Beam Angle	150°
IP Rating	IP67 Plus [Wet]

Request pricing & availability

Request a product quote at truled.com

Include any configuration reference, quantities, required lengths and project location.

A configuration reference identifies a published specification row. A row may list multiple options; it is not confirmation that every option is included. This sheet is not an installation instruction or an approved project submittal.