WHITE LIGHT STRIPS

White IP67 24V 12mm LED strip

TRU-SW24V12MM304LEDM

White IP67 24V 12mm LED strip. Review the dimensions and electrical ratings for your installation.

Use this catalog sheet to discuss your project. Final dimensions, ratings, certifications and available configurations must be confirmed for the selected product.



Product specifications

Truled part number	TRU-SW24V12MM304LEDM
Category	LED strips
Product type	White light strips

Configuration reference

TRU-SW24V12MM304LEDM-A

Dimension	L5000*W12*H4.5mm [L197*W0.47*H0.18in.]
Increment	26.3mm [1.04in.]
LED Type	SMD 2835
LED Qty	304LED/M [92LED/ft.]
Voltage	24VDC
Power	14W/M [4.3W/ft.]
CCT / Wavelength	2700K±120K 3000K±150K 3500K±300K 4000K±300K 5000K±400K 6500K±500K (3 step SDCM in 1 bin)
Brightness @CRI80&4000K	2140lm/M [652lm/ft.]
Light Efficiency @CRI80&4000K	153lm/W
Brightness @CRI90&4000K	1820lm/M [555lm/ft.]
Light Efficiency @CRI90&4000K	130lm/W
Beam Angle	150° (perpendicular to the LED strip) & 110° (parallel to the LED strip)
IP Rating	IP67 [Wet]

Configuration reference

TRU-SW24V12MM304LEDM-B

Dimension	L5000*W12*H4.5mm [L197*W0.47*H0.18in.]
Increment	26.3mm [1.04in.]
LED Type	SMD 2835
LED Qty	304LED/M [92LED/ft.]
Voltage	24VDC
Power	19W/M [5.8W/ft.]
CCT / Wavelength	2700K±120K 3000K±150K 3500K±300K 4000K±300K 5000K±400K 6500K±500K (3 step SDCM in 1 bin)
Brightness @CRI80&4000K	2910lm/M [887lm/ft.]
Light Efficiency @CRI80&4000K	153lm/W
Brightness @CRI90&4000K	2470lm/M [753lm/ft.]
Light Efficiency @CRI90&4000K	130lm/W
Beam Angle	150° (perpendicular to the LED strip) & 110° (parallel to the LED strip)
IP Rating	IP67 [Wet]

Request pricing & availability

Request a product quote at truled.com

Include any configuration reference, quantities, required lengths and project location.

A configuration reference identifies a published specification row. A row may list multiple options; it is not confirmation that every option is included. This sheet is not an installation instruction or an approved project submittal.