WHITE LIGHT STRIPS

170lm/W 24V 64LED/M 10mm LED strip

TRU-SWA24V10MM64LEDM

170lm/W 24V 64LED/M 10mm LED strip. Review the dimensions and electrical ratings for your installation.

Use this catalog sheet to discuss your project. Final dimensions, ratings, certifications and available configurations must be confirmed for the selected product.



Product specifications

Truled part number	TRU-SWA24V10MM64LEDM
Category	LED strips
Product type	White light strips

Configuration reference

TRU-SWA24V10MM64LEDM-A

Dimension	L5000*W10*H1mm [L197*W0.4*H0.04in]
Increment	125mm [4.92in]
LED Type	SMD2835
LED Qty	64LED/M [20LED/ft.]
Voltage	24VDC
Power	7W/M [2.13W/ft.]
CCT / Wavelength	2700K 3000K 3500K 4000K 5000K 6500K
Brightness @4000K&CRI80	1090lm/M [330lm/ft.]
Light Efficiency @4000K&CRI80	155lm/W
Brightness @4000K&CRI90	Not specified
Light Efficiency @4000K&CRI90	Not specified
Beam Angle	120°
IP Rating	IP20/ IP54/ IP54 Plus/ IP65/ IP67/ IP67 Plus/ IP68 [Dry/Damp/Wet]

Configuration reference

TRU-SWA24V10MM64LEDM-B

Dimension	L5000*W10*H1mm [L197*W0.4*H0.04in]
Increment	125mm [4.92in]
LED Type	SMD2835
LED Qty	64LED/M [20LED/ft.]
Voltage	24VDC
Power	7W/M [2.13W/ft.]
CCT / Wavelength	2700K 3000K 3500K 4000K 5000K 6500K
Brightness @4000K&CRI80	1190lm/M [360lm/ft.]
Light Efficiency @4000K&CRI80	170lm/W
Brightness @4000K&CRI90	Not specified
Light Efficiency @4000K&CRI90	Not specified
Beam Angle	120°
IP Rating	IP20/ IP54/ IP54 Plus/ IP65/ IP67/ IP67 Plus/ IP68 [Dry/Damp/Wet]

Configuration reference

TRU-SWA24V10MM64LEDM-C

Dimension	L5000*W10*H1mm [L197*W0.4*H0.04in]
Increment	125mm [4.92in]
LED Type	SMD2835
LED Qty	64LED/M [20LED/ft.]
Voltage	24VDC
Power	10W/M [3.05W/ft.]
CCT / Wavelength	2700K 3000K 3500K 4000K 5000K 6500K
Brightness @4000K&CRI80	1550lm/M [470lm/ft.]
Light Efficiency @4000K&CRI80	155lm/W
Brightness @4000K&CRI90	Not specified
Light Efficiency @4000K&CRI90	Not specified
Beam Angle	120°
IP Rating	IP20/ IP54/ IP54 Plus/ IP65/ IP67/ IP67 Plus/ IP68 [Dry/Damp/Wet]

Configuration reference

TRU-SWA24V10MM64LEDM-D

Dimension	L5000*W10*H1mm [L197*W0.4*H0.04in]
Increment	125mm [4.92in]
LED Type	SMD2835
LED Qty	64LED/M [20LED/ft.]
Voltage	24VDC
Power	10W/M [3.05W/ft.]
CCT / Wavelength	2700K 3000K 3500K 4000K 5000K 6500K
Brightness @4000K&CRI80	1700lm/M [520lm/ft.]
Light Efficiency @4000K&CRI80	170lm/W
Brightness @4000K&CRI90	Not specified
Light Efficiency @4000K&CRI90	Not specified
Beam Angle	120°
IP Rating	IP20/ IP54/ IP54 Plus/ IP65/ IP67/ IP67 Plus/ IP68 [Dry/Damp/Wet]

Configuration reference

TRU-SWA24V10MM64LEDM-E

Dimension	L5000*W10*H1mm [L197*W0.4*H0.04in]
Increment	125mm [4.92in]
LED Type	SMD2835
LED Qty	64LED/M [20LED/ft.]
Voltage	24VDC
Power	8.3W/M [2.5W/ft.]
CCT / Wavelength	2700K 3000K 3500K 4000K 5000K 6500K
Brightness @4000K&CRI80	Not specified
Light Efficiency @4000K&CRI80	Not specified
Brightness @4000K&CRI90	1090lm/M [330lm/ft.]
Light Efficiency @4000K&CRI90	132lm/W
Beam Angle	120°
IP Rating	IP20/ IP54/ IP54 Plus/ IP65/ IP67/ IP67 Plus/ IP68 [Dry/Damp/Wet]

Configuration reference

TRU-SWA24V10MM64LEDM-F

Dimension	L5000*W10*H1mm [L197*W0.4*H0.04in]
Increment	125mm [4.92in]
LED Type	SMD2835
LED Qty	64LED/M [20LED/ft.]
Voltage	24VDC
Power	8.3W/M [2.5W/ft.]
CCT / Wavelength	2700K 3000K 3500K 4000K 5000K 6500K
Brightness @4000K&CRI80	Not specified
Light Efficiency @4000K&CRI80	Not specified
Brightness @4000K&CRI90	1190lm/M [360lm/ft.]
Light Efficiency @4000K&CRI90	145lm/W
Beam Angle	120°
IP Rating	IP20/ IP54/ IP54 Plus/ IP65/ IP67/ IP67 Plus/ IP68 [Dry/Damp/Wet]

Configuration reference

TRU-SWA24V10MM64LEDM-G

Dimension	L5000*W10*H1mm [L197*W0.4*H0.04in]
Increment	125mm [4.92in]
LED Type	SMD2835
LED Qty	64LED/M [20LED/ft.]
Voltage	24VDC
Power	12W/M [3.7W/ft.]
CCT / Wavelength	2700K 3000K 3500K 4000K 5000K 6500K
Brightness @4000K&CRI80	Not specified
Light Efficiency @4000K&CRI80	Not specified
Brightness @4000K&CRI90	1550lm/M [470lm/ft.]
Light Efficiency @4000K&CRI90	132lm/W
Beam Angle	120°
IP Rating	IP20/ IP54/ IP54 Plus/ IP65/ IP67/ IP67 Plus/ IP68 [Dry/Damp/Wet]

Configuration reference

TRU-SWA24V10MM64LEDM-H

Dimension	L5000*W10*H1mm [L197*W0.4*H0.04in]
Increment	125mm [4.92in]
LED Type	SMD2835
LED Qty	64LED/M [20LED/ft.]
Voltage	24VDC
Power	12W/M [3.7W/ft.]
CCT / Wavelength	2700K 3000K 3500K 4000K 5000K 6500K
Brightness @4000K&CRI80	Not specified
Light Efficiency @4000K&CRI80	Not specified
Brightness @4000K&CRI90	1700lm/M [520lm/ft.]
Light Efficiency @4000K&CRI90	145lm/W
Beam Angle	120°
IP Rating	IP20/ IP54/ IP54 Plus/ IP65/ IP67/ IP67 Plus/ IP68 [Dry/Damp/Wet]

Request pricing & availability

Request a product quote at truled.com

Include any configuration reference, quantities, required lengths and project location.

A configuration reference identifies a published specification row. A row may list multiple options; it is not confirmation that every option is included. This sheet is not an installation instruction or an approved project submittal.